



VERMONT

Environmental Guide for Vehicle Service

A GUIDE FOR

Vehicle Service | Municipalities | Urban Transit Authorities
Auto Dealerships | Contractors | Charter Buses
Fleet Maintenance | Taxi & Limousines | Marinas
General Freight Trucking | Motorcycle Dealer & Repair
Snowmobile Dealer & Repair | Small Engine Repair
Couriers | Utilities | Towing | Ski Areas

Revised 2016

 **VERMONT**
AGENCY OF NATURAL RESOURCES
Department of Environmental Conservation

Resource Contact List

This guide has been developed by the Environmental Assistance Office (EAO), a non-regulatory office within the Vermont Department of Environmental Conservation (DEC). Our services include: hotline assistance, on-site assessments, workshops and trainings, environmental recognition programs, and waste reduction assistance. These services are confidential and provided at no cost.

If you are planning new construction or modifications to your facility, contact EAO's Permit Specialists to see what state permits you may need (in addition to contacting your municipal office for local ordinances and permitting requirements). See Appendix D for information on how to contact the Permit Specialists in your area.

Environmental Assistance Office, Vermont Department of Environmental Conservation

1 National Life Drive, Main 2, Montpelier, VT 05620-3804
800-974-9559

ADDITIONAL CONTACTS

HAZARDOUS WASTE, SOLID WASTE, MEDICAL WASTE, USED OIL, UNIVERSAL WASTE & TANKS (UNDERGROUND/ABOVEGROUND)

Waste Management & Prevention Division
Department of Environmental Conservation
1 National Life Drive, Davis 1
Montpelier, VT 05620-3704
802-828-1138

TO REPORT HAZARDOUS MATERIAL SPILLS

Waste Management & Prevention Division
Regular Business Hours: 802-828-1138

Emergency Management Hotline
24 Hours/7 Days: 800-641-5005

AIR EMISSIONS, DUST, NOISE, SMOKE OR OUTDOOR BURNING CONCERNS

Air Quality & Climate Division
Department of Environmental Conservation
1 National Life Drive, Davis 2
Montpelier, VT 05620-3802
802-828-1288

COMMUNITY RIGHT-TO-KNOW REPORTING, EMERGENCY RESPONSE

Department of Public Safety
Division of Emergency Management and Homeland Security
Community Right to Know/Tier II Program
103 South Main Street
Waterbury, VT 05671-2101
802-244 8721 or 800-347-0488
<http://demhs.vermont.gov/index.php>

WASTEWATER, SEPTIC SYSTEMS, FLOOR DRAINS

Drinking Water and Groundwater Protection Division
Department of Environmental Conservation
See Appendix D - Regional Office Map for contacts serving your town

PESTICIDES, HERBICIDES

Agency of Agriculture, Food and Markets
116 State Street
Montpelier, VT 05620-2901
802-828-2431
<http://agriculture.vermont.gov/>

ASBESTOS AND LEAD-ABATEMENT

Department of Health
108 Cherry Street
Burlington, VT 05402
800-439-8550 or 802-863-7220
<http://healthvermont.gov/enviro/asbestos/asbestos.aspx>

VOSHA, OCCUPATIONAL HEALTH & SAFETY

Department of Labor
5 Green Mountain Drive
Montpelier, VT 05601-0488
802-828-2765 or 800-287-2765
<http://labor.vermont.gov/vosha/>

DRINKING WATER, WATER SUPPLY

Drinking Water and Groundwater Protection Division
Department Environmental Conservation
1 National Life Drive, Davis 2
Montpelier, VT 05602-3521
800-823-6500

STORMWATER, WATER QUALITY, WETLANDS, RIVER MANAGEMENT, STREAM ALTERATIONS

Watershed Management Division
Department of Environmental Conservation
1 National Life Drive, Davis 2
Montpelier, VT 05602-3522
802-828-3522

ENVIRONMENTAL ENFORCEMENT

Environmental Enforcement Office
Department of Environmental Conservation
1 National Life Drive, Davis 2
Montpelier, VT 05620-3803
802-828-1254

ACT 250 OFFICE

Natural Resources Board (NRB)
1 National Life Drive, Dewey 1
Montpelier, VT 05620-3201
802-828-3309
<http://nrb.state.vt.us/>

NRB Staff Contacts

<http://nrb.state.vt.us/staff.htm>

US EPA REGION I/NEW ENGLAND

The Customer Call Center can answer questions about everything EPA does, and will refer you to their appropriate staff, when necessary.

EPA New England - Customer Call Center (New England States)

888-372-7341
fax: 617-918-0101

<https://www.epa.gov/aboutepa/epa-region-1-new-england>

How To Use This Guide

The *Vermont Environmental Guide for Vehicle Service* is divided into three sections – **GUIDANCE, FACT SHEETS AND APPENDICES**. The **GUIDANCE** section provides self-audit checklists which cover regulatory requirements and BMPs for vehicle service facilities including:

- Hazardous Waste
- Wastewater and Floor Drains
- Air Pollution
- Petroleum Storage

Each of these self-audit checklists can be used to determine whether your facility is in compliance with Vermont’s environmental regulations on a given topic. The checklist questions are worded such that if you answer “Yes” or “Not Applicable (N/A),” you are likely to be in compliance with that specific requirement. If your answer is “No,” we recommend you revisit the regulatory issue being addressed and review any associated environmental Fact Sheets to learn more about how to fix the issue.

Throughout the first section of the guide, you will find many best management practices (BMPs) indicated by the following symbol .

The **FACT SHEET** section of the guide is comprised of 24 environmental Fact Sheets, each of which is a quick reference on wastes and other subjects common to vehicle service operations. The Fact Sheets provide compliance information as well as best management practices and are a great place to start when you need to be reminded of specific details on a given topic.

Lastly, there are 10 **APPENDICES** in the Guide that include example forms, solid waste district information and permitting resources.

Table of Contents

COMPLIANCE CHECKLISTS & GUIDANCE

Helpful Tips For Environmental Success	7
Hazardous Waste	9
Wastewater and Floor Drains	16
Air Pollution.....	20
Petroleum Storage	24

FACT SHEETS

FS1	Aqueous Parts Cleaning.....	30
FS2	Asbestos Containing Auto Parts	33
FS3	Burning Used Oil Fuel.....	36
FS4	Hazardous Material Spill Response.....	39
FS5	Making a Hazardous Waste Determination.....	42
FS6	Materials Banned From Vermont Landfills	45
FS7	Lead-Acid Batteries	47
FS8	Managing Air Bags	49
FS9	Managing Automotive Antifreeze	52
FS10	Managing Waste Fuel and Fuel/Water Mixtures.....	55
FS11	Mercury Containing Lamps & Auto Switches	57
FS12	Motor Vehicle Air Conditioning	60
FS13	Oil Filters	62
FS14	Oily Wastes	64
FS15	Oil/Water Separators	67
FS16	Petroleum-Based Parts Cleaning	69
FS17	Scrap Metal, Recycling, and Landfill Disposal Bans	72

Table of Contents

FS18	Scrap Tires.....	74
FS19	Shop Rags Contaminated with Used Oil or Hazardous Waste	76
FS20	Federal Spill Prevention, Control, and Countermeasure Regulation	79
FS21	Universal Waste.....	81
FS22	Used Oil.....	83
FS23	Washwater Discharges From Vehicle Washing	86
FS24	Waste Motor Vehicle Fuel and System Components	88

APPENDICES

Appendix A	Common OSHA Violations for Vehicle Service Shops.....	91
Appendix B	Hazardous Chemical Decision Diagram for Tier II Reporting.....	93
Appendix C	Vermont Solid Waste Management Entities	94
Appendix D	Regional Office Map	95
Appendix E	Permit and License Information (new construction or existing)	96
Appendix F	Common Listed and Characteristic Hazardous Waste.....	98
Appendix G	Procedure Addressing the Management and Disposal of Aerosol Cans	100
Appendix H	VT Hazardous Waste Handler Site ID Form Example	104
Appendix I	Hazardous Waste Compatibility List	107
Appendix J	Hazardous Waste Manifest Information & Form Example	109

Helpful Tips For Environmental Success

Keep Good Records

Keep receipts, bills of lading, and hazardous waste manifests every time you buy products containing hazardous substances or dispose of hazardous waste. Even when not required by regulation, well-kept records can help you track materials used and waste generated, expedite a property sale or secure a loan, ultimately reducing your liability.

Involve and Train Your Staff

When setting up waste management and worker safety programs, involvement of the entire staff will produce better results in the long run. Make sure employees know that their ideas are welcome. In so doing, you help ensure that the programs you design will work at your facility. An investment in employee training can produce less waste, a more efficient process and fewer accidents. Common OSHA violations in Vehicle Service Shops can be found in Appendix A.

Be Careful What You Throw in the Dumpster or Pour Down the Drain

Hazardous substances should never be disposed of with the regular trash or poured down the drain. Certain wastes generated from the servicing of vehicles such as paints, liquids in general, tires, batteries and oil soaked materials are banned from Vermont landfills. Although certified hazardous waste haulers can be used, most municipal solid waste districts and alliances can help with recycling and disposal options for these materials.

Keep Hazardous Materials and Service Activities Away from Floor Drains

Repair vehicles in areas with no floor drains or in areas where floor drains are plugged or covered. Hazardous materials in wastewater discharges from floor drains can lead to ground water and soil contamination, or cause problems at the local wastewater treatment plant. Some facilities use temporary or locking drain plugs on their floor drains.

Maintain and Know How to Use Your Safety Data Sheets (SDS)

All chemical products have an associated SDS (formerly known as MSDS) that details important environmental, health and workplace safety information. Reviewing a product's SDS before making a purchase will alert you to possible concerns and perhaps help avoid a problem down the road. SDS are required to be kept on-site and should be readily accessible by employees and organized in such a way that it is easy to find the sheet for a given product. Maintain and update your SDS on a regular basis. Chemicals that are accompanied by an SDS may be subject to Emergency Planning and Community Right-to-Know Act Tier II reporting (Tier II Reporting). A Hazardous Chemical Decision Diagram for Tier II Reporting is provided in Appendix B.

Keep It Off the Floor

Spills, leaks and drips of vehicle fluids can lead to clean-up and disposal costs. Reduce the need to clean your floors and minimize the use of oil soaking absorbents. Consider using pans to help catch drips and leaks, and use funnels when transferring or changing vehicle fluids.

Reuse and Recycle Whenever Possible

Certain wastes generated at vehicle service facilities may be able to be reused or recycled. Learn more about reuse and recycling options for certain wastes in the Fact Sheet section of this guide book and from your local solid waste district. A map of Vermont Solid Waste Management Entities is located in Appendix C.

Take Advantage of No-Cost Assistance Programs

In the face of increasing costs and an ever-changing regulatory landscape, it is difficult for owners and operators to keep track of all the applicable requirements affecting vehicle service facilities. Take advantage of low and no- cost workshops and training events that are available to help you comply with these requirements and give yourself more time to do the primary job of running a business. To contact a Permit Specialist, refer to the Regional Office Map in Appendix D. A summary of additional permit and licensing information can be found in Appendix E.

Use Prevention Strategies to Reduce Waste and Minimize Regulatory Oversight

A tried-and- true pollution prevention strategy is to assess the feasibility of a change in “process” that might produce both environmental and worker safety benefits. For example, do you really need that parts washer? And if so, are there solvents or other techniques that could be used that offer such advantages when compared to traditional petroleum-based solvents?

Properly Label Waste Containers and Keep in One Area

Keep containers used to store waste in one area to minimize the potential for accidental spills and to provide the best opportunity for efficient management. Be sure to label all waste containers with descriptive wording that identifies the contents. Inspectors commonly find waste containers that are improperly labeled. Don't label containers with the words “Hazardous Waste” if the waste is being managed under an exemption (e.g., used antifreeze that will be recycled). While not a violation, calling something a “hazardous waste” that may not be can add to your facility's monthly generation total. Please see the Hazardous Waste Checklist and individual Fact Sheets in this Guide for more information.

Hazardous Waste

Vehicle service facilities typically generate several waste streams which require special management as hazardous waste, used oil or universal waste. From the very start, it is important to understand that less is better. When a facility only generates small amounts of hazardous waste (i.e., less than 220 pounds per month), it is subject to fewer regulations and may incur lower waste management costs. In order to determine how wastes should be managed, a vehicle service facility shop should follow these steps:

Step 1: Determine whether any wastes are exempt.

Many of the hazardous wastes generated by vehicle service operations may be exempt from full regulation as hazardous waste. Why is this important? Generally, it is easier and less costly to manage wastes under their respective exemptions than to manage them as hazardous waste. **TO TAKE ADVANTAGE OF THE EXEMPTIONS, EACH WASTE MUST BE MANAGED ACCORDING TO SPECIFIC CONDITIONS. IT IS IMPORTANT TO KNOW THAT EXEMPT WASTES DO NOT HAVE TO BE COUNTED WHEN CALCULATING HOW MUCH HAZARDOUS WASTE YOUR FACILITY GENERATES PER MONTH.** It is the weight of hazardous waste generated each calendar month that determines your “generator status,” which in turn dictates the scope of regulatory requirements with which you must comply (see Step 3). The following wastes may be managed as exempt provided specific conditions are followed:

- Used Oils – crankcase/transmission/hydraulic
- Used Oil Filters
- Contaminated Shop Rags (that are destined for commercial laundering)
- Spent Antifreeze
- Lead Acid and NiCad Rechargeable Batteries (not including standard alkaline batteries which may be recycled as part of the Call 2 Recycle Program (<http://www.call2recycle.org>))
- Gas Filters (only metal encased)
- Mercury Switches (trunk & hood lights, and ABS sensors)
- Fluorescent & HID Lamps
- Chlorofluorocarbon (CFC) Refrigerants
- Waste Fuel & Fuel-Water Mixtures

Fact Sheets dealing with these and other specific vehicle service waste streams are found in this Guide. The Fact Sheets explain how each of the above must be managed in order for the waste to be considered “exempt.” **YOU SHOULD REVIEW THE FACT SHEET FOR EACH OF THE POTENTIALLY EXEMPT HAZARDOUS WASTES YOUR FACILITY GENERATES TO MAKE SURE THAT YOUR MANAGEMENT PRACTICES ARE CONSISTENT WITH THE PRACTICES REQUIRED BY THE EXEMPTIONS.**



Disposable oil soaking absorbents such as pads, towels or granular types can be reused several times, even wrung out, after each use.

Step 2: Determine if the waste is “listed” as a hazardous waste or exhibits any of the hazardous waste “characteristics.”

In general, waste is regulated as hazardous waste if it is specifically “listed” in the regulations, or if it exhibits at least one of four hazardous waste “characteristics” – ignitability, corrosivity, reactivity or toxicity. Therefore, for each waste, a generator needs to determine if the waste is on one of the “lists” in Vermont’s Hazardous Waste Management Regulations or if the waste exhibits any of the above characteristics. For more information see Appendix F: “Common Listed and Characteristic Hazardous Waste” and also, the FACT SHEET - FS5 “Making a Hazardous Waste Determination.” The generator’s own knowledge of how the waste is generated, review of applicable Safety Data Sheets and when necessary, laboratory testing, are all key factors that can be relied upon in assessing whether a waste is a hazardous waste (or not).

REGULATORY REQUIREMENT

Making the correct hazardous waste determination is very important because it is the foundation for being in compliance. However, it can sometimes be difficult. If you are unsure about your determination(s), or need assistance making a hazardous waste determination, please contact: the Environmental Assistance Office at 800-974-9559.

Step 3: Determine your “generator status.”

The following table lists hazardous wastes commonly generated by vehicle service and was designed to help you calculate how many pounds of hazardous waste are generated at your facility per month. To use the table:

1. Review the list of hazardous waste streams in the first column and indicate which, if any, you generate in the fourth column titled “Do I Generate This Waste?” For your reference, applicable Fact Sheets (FS) are noted in the first column next to the waste streams.
2. For each waste that is generated, use the last column to account for how many pounds are generated per month. In the absence of the exact weight, liquid hazardous waste expressed in gallons may be approximated in pounds by multiplying by 8 (the specific gravity of water is 8.2 lbs/gallon). If you determined in Step 1 that a particular waste stream is exempt, simply write “E” in the last column. Potentially exempt wastes are found in the shaded cells of the table.
3. Once you have recorded the amount in pounds of each hazardous waste generated per month, total the last column and record the sum at the bottom in the “Total” box.

Waste streams shown in **red type** may or may not be hazardous. See the discussion in Step 2 on making a hazardous waste determination.

Regulated Wastes Typically Generated by Vehicle Service Operations	Typical Waste Code	Likely Hazardous Property	Do I Generate This Waste? (Y=yes N=no)	How Many Pounds Do I Generate Per Month? (E=exempt)
Oils - Crankcase/ Transmission/Hydraulic (FS3 and FS22)	N/A - Used Oil	A petroleum distillate, suspected carcinogen.		
Oil Filters (FS13)	VT02	Petroleum content >5% by weight.		
Oil-Soaked Absorbents— i.e., socks, pads, “speedi-dry” (FS14)	VT02	Petroleum content >5% by weight.		
Contaminated Shop Rags (FS19)	VT02, D001, F002, F003, F005	Petroleum content >5% by weight, often ignitable.		
Petroleum Based Cleaning Solution (FS16)	VT02, D001	Petroleum content >5% by weight, often ignitable.		
Aqueous Parts Cleaning Solution (FS1)	VT02, D008	Petroleum content >5% by weight, toxic metals.		
Antifreeze (FS9)	VT08, D008 D018	Ethylene Glycol, toxic heavy metals.		
Lead Acid Batteries (FS7)	D002, D008	Lead, Corrosive		
Gas Filters	D001, D018	Ignitable, Benzene		
Contaminated Gasoline (FS24)	D001, D018	Ignitable, Benzene		
Contaminated Diesel (FS24)	VT02, D001	Petroleum content >5% by weight, often ignitable.		
Paints & Paint Related Materials	D001, F003, F005, D035	Often have ignitable or toxic solvents. Some colored paints contain toxic metals.		
Various Spray Cans with Remaining Product	D001, F003, F005	Often have ignitable or toxic solvents.		
Oil Water Mixture (FS10)	VT02	Petroleum content >5% by weight.		
Floor Drain Sludge (FS15)	VT02	Petroleum content >5% by weight.		
Mercury Switches (FS11)	D009 or Universal Waste	Mercury		
Mercury Fluorescent Lamps (FS11)	D009 or Universal Waste	Mercury		
Chlorofluorocarbon Refrigerants (FS12)	Characteristic	Toxicity		

TOTAL

I know how much hazardous waste I generate per month. What's Next?

By now you hopefully have a good idea about which wastes are regulated as hazardous wastes. You should also have an estimate (or actual number) for each hazardous waste your facility generates (in pounds) per month. Remember, the weight of exempt wastes are not included in monthly generation totals.

If your facility generates less than 220 pounds of hazardous waste per month, it is regulated as a Conditionally Exempt Generator (CEG). Requirements for CEGs are minimal when compared to the requirements for businesses that generate 220 pounds or more of hazardous waste per month. **MOST VEHICLE SERVICE FACILITIES ARE ABLE TO QUALIFY AS A CEG.** If your facility does not qualify as a CEG, you should investigate whether best management practices presented in this Guide, especially the Fact Sheets, can help lower your monthly hazardous waste generation rate. Remember, less is better.

If your facility generates 220 pounds or more of hazardous waste per month, it is either a Small Quantity Generator or a Large Quantity Generator. In this case, contact the Environmental Assistance Office or the Waste Management & Prevention Division's Hazardous Waste Program for information about the requirements that apply to your generator status.

Self Audit Checklist for Conditionally Exempt Generators of Hazardous Waste

THE FOLLOWING CHECKLIST IS FOR CEGS ONLY. It summarizes CEG requirements, and will help you determine if you are in compliance with Vermont's hazardous waste regulations. The statements are worded such that a "No" response indicates a potential compliance issue.

-
1. We have evaluated all of our wastes and determined which are "hazardous wastes."

Yes No

-
2. We have calculated our monthly hazardous waste generation rate and determined that we are either a Conditionally Exempt Generator (less than 220 pounds/month) OR that we are a fully regulated small quantity (SQG) or large quantity (LQG) generator of hazardous waste.

Yes No



Any Vermont listed waste (i.e., waste assigned a hazardous waste code beginning with "VT") can be averaged over a six month period. For example, the weight of absorbent materials used to soak up oil (waste code "VT02") after a spill can be equally apportioned over six months.



Remember, the weight of waste(s) managed under an exemption does not count towards your monthly total.

-
3. We have filed a *Hazardous Waste Handler Site ID Form* with the Waste Management & Prevention Division.

Yes No



Any facility generating any amount of hazardous waste is required to file a “Hazardous Waste Handler Site ID” form with the Waste Management & Prevention Division (WMPD). After receipt of the form, the WMPD will assign your facility a site- specific EPA Identification Number. Please see the sample form in Appendix H. If you are unsure whether your facility has filed this form, contact the EAO.

-
4. All of our hazardous waste is stored in containers that are:

- In good condition and chemically compatible with the waste stored in them;
- Closed except to add or remove waste;
- Marked with the words “Hazardous Waste” and other words that identify the contents (e.g., “oily debris” or “solvent”);
- Located on an impervious surface;
- Kept under cover to protect from rain and snow;
- Protected from freezing (applicable for freezable wastes)

Yes No



A drum mounted funnel **MUST** be covered for a container to be considered closed.

TIP: Allowing waste solvent to evaporate is prohibited as illegal disposal of a hazardous waste.

5. Incompatible wastes are:

- Not placed in the same container (or in an unwashed container that once held an incompatible waste);
- Stored in containers that are separated from each other by means of a berm, wall or other device.

Yes No



See Appendix I for the “Hazardous Waste Compatibility List.”

6. We do not store more than 2,200 pounds of hazardous waste on-site at any one time.

Yes No



If at any time more than 2,200 pounds of hazardous waste is stored on-site (roughly equivalent to five 55-gallon drums of a liquid waste), you no longer qualify as a CEG and become subject to all the requirements of a fully regulated (SQG or LQG) generator.

7. The management of hazardous waste at our facility is conducted in a manner that minimizes the possibility of fire, explosion or any release of hazardous waste which could threaten human health or the environment.

Yes No

8. In the event of a release of hazardous waste to the environment, we comply with applicable reporting and emergency response procedures. (See FACT SHEET - FS4 “Hazardous Materials Spill Response” for additional information.)

Yes No

9. We utilize our solid waste district for hazardous waste disposal, or ship our hazardous waste to a certified treatment, storage or disposal facility using a licensed hazardous waste transporter. (Other management/disposal options may apply – contact the Environmental Assistance Office or the Hazardous Waste Management Program for more information.)

Yes No



If self-transporting hazardous waste, be aware of any applicable Federal Department of Transportation regulations. Waste must be transported in a vehicle owned by the CEG or an employee of the CEG. For Hazardous Waste Manifest Information & Form Example see Appendix J.

10. We have read all of the applicable Fact Sheets related to the hazardous wastes we generate at our facility and are managing our equipment, materials and waste as described in these Fact Sheets.

Yes No

BEST MANAGEMENT PRACTICES

Although not specifically required by the hazardous waste regulations for CEGs, consider the following BMPs:

- Store liquid wastes away from floor drains;
- Store hazardous waste in one location (makes it easier to keep track of) ;
- Periodically inspect waste containers for leaks;
- Consider using covered funnels, containment pallets and drip pans to minimize the chance for spills;
- Provide training to your employees about proper waste management and spill response.

SUMMARY OF IMPORTANT POINTS

- Take advantage of the exemptions, but make sure your management practices are consistent with the required conditions.
- Make correct hazardous waste determinations - this is the foundation for being in compliance.

Wastewater and Floor Drains

Wastewater discharges are regulated by the Department of Environmental Conservation's Drinking Water and Groundwater Protection Division. A wastewater permit is required for any sanitary discharge (toilets, sinks, showers, etc.) from a public building to either a municipal treatment plant or an on-site subsurface system unless the discharge began prior to 1970. Any new wastewater connection or new use of an existing connection may also require a permit from one of DEC's five Regional Offices. See Appendix D to identify the Regional Office serving your town and to obtain contact information.

In addition to sanitary wastewater, other common discharges associated with the servicing of vehicles include snow melt, wastewater from cleaning floors and vehicle washing. Often wastewater enters a floor drain which may be piped to a municipal treatment plant, an on-site disposal system like a septic tank and leach field, a rock "drywell" or perhaps to the ground surface. If you have a floor drain, it is imperative that you know where any water entering the drain is ultimately discharged.

FLOOR DRAINS

The Drinking Water and Groundwater Protection Division's Underground Injection Control (UIC) program adopted new regulations in 2014 affecting floor drains. In general, floor drains are *prohibited* at vehicle service facilities unless they are connected to either a municipal wastewater treatment facility or to a holding tank.

The only exception to the prohibition is where the floor drain discharges only **SNOW MELT OR LIMITED WASHWATER** from the exterior washing of vehicles AND the floor drain is located in an area that is physically isolated from the rest of the shop such that any oils, fuel, antifreeze, solvents or any other liquid chemicals are not stored or present in the area of the floor drain, and could not possibly enter the floor drain in the event of an accidental spill.

For vehicle snow melt or washwater to be discharged:

- To the **SUBSURFACE**, a wastewater/potable water supply permit will be required if the discharge is combined with sanitary wastewater, (e.g., septic/leach field disposal system). An individual UIC permit will be required, with conditions, if the discharge is subsurface but not to a wastewater system (e.g., drywell or dedicated leach field).
- To the **GROUND SURFACE**, a practice referred to as "daylighting," see FACT SHEET - FS23 of this Guide on: **WASHWATER DISCHARGES FROM VEHICLE WASHING**. Among other conditions where a floor drain is used, the Fact Sheet specifies that 1) washwater from no more than 30 vehicles per week can be daylighted, 2) an oil-water separator on the floor drain piping system must be installed, and 3) only non-phosphorus soaps can be used.

NOTE: Changes to the current UIC Rules effective October 29, 2014 are being drafted that will clarify and expand on certain sections within the Rule, including; vehicle washing discharges, the registration process for floor drains, and how snow melt water can be handled, among other things.

Owners and operators of facilities with floor drains will have an opportunity to comment on the proposed changes when they are released in final draft as part of the rule amendment process.

Self Audit Checklist for Floor Drains

The following checklist summarizes basic wastewater requirements and will help you determine if you are in compliance. The statements are worded such that a “No” response indicates a likely compliance problem.

-
1. If our floor drain discharges to the municipal treatment plant, we have received approval from the local sewer authority.

Yes No N/A



A floor drain located in an area where vehicles are serviced or where hazardous materials are stored is **PROHIBITED** unless it is connected to either the municipal sewer or a holding tank.

-
2. If our floor drain discharges to the municipal treatment plant, we operate and maintain an oil/water separator on the floor drain piping system if required by our municipal sewer ordinance or other local sewer authority.

Yes No N/A



It is important to keep maintenance and service records for any oil/water separator. Separators should be inspected annually and cleaned as needed. If an accidental spill of a hazardous material enters a separator, it should be cleaned immediately. Refer to FACT SHEET - FS15 “Oil/Water Separators” for more information.

-
3. If our floor drain discharges *only* vehicle washwater and/or snowmelt to the ground surface, the floor drain is located in an area that is physically isolated so there is no chance of any chemicals, vehicle fluids, fuels or other hazardous liquids entering the drain. (See FACT SHEET - FS23 “Washwater Discharges From Vehicle Washing”.)

Yes No N/A



Areas that are physically isolated from service bays to allow for the discharge of snowmelt cannot be used to store hazardous materials or oils.

4. Our facility does not dispose of any waste oil, antifreeze, solvents or other hazardous materials in sinks or floor drains.

Yes No N/A

FLOOR DRAIN BEST MANAGEMENT PRACTICES

- We recommend that all onsite discharges (subsurface or daylighted) from floor drains at vehicle service facilities be registered with the UIC program now, to avoid compliance problems in the future once the UIC Rule is amended. A new online registration system is available at the Vermont UIC Program webpage.
- Even when not required, use of a sand/grit collector and oil/water separator represent a BMP whenever floor drain wastewater is generated at a vehicle service facility. Use of a separator would likely be required where discharges go to a holding tank and contents are pumped for transport to a municipal plant for treatment and disposal or where the discharge goes directly to the municipal sewer.
- Keep spill clean-up materials readily available and make sure employees know proper response procedures.
- Keep floors as clean as possible. Sweep floors to minimize the need to wash with water. For small spills and leaks, use reusable shop rags, wet-vacuums, drip pans, etc. to avoid the use of absorbents that typically result in generation of a hazardous waste. See FACT SHEET - FS14: "Oily Wastes."

STORMWATER

The quality of our surface waters is continually under pressure as development and associated sources of pollution grow. The number one stormwater impact on our lakes and rivers is sediment. Although vehicle service facilities are not required to get a permit for stormwater discharges at this time, ultimately you are responsible for polluted stormwater that runs off your site and reaches lakes and rivers.

A good way to approach stormwater management at your facility is to divide the outside grounds surrounding your facility into sections. It is often easier to address those sections individually, rather than trying to address stormwater discharges as a whole. A little work now may help in the long run in dealing with stormwater at your site.



You may need a stormwater permit at your facility if you are planning any construction or are considering expanding your parking area. If you plan to expand your main facility or add additional pole barns or storage buildings you may trigger the need for a construction stormwater permit. By increasing impervious surfaces (i.e., paving and buildings) you may also trigger the need for a stormwater permit after construction is complete. See Appendix J for contact information.

STORMWATER BEST MANAGEMENT PRACTICES

- Encourage stormwater to discharge in sheet flow to vegetated and grassy areas rather than channel flow to one or a few discharge points.
- Implement methods to slow discharge water down, and break up the flow of water. Such activities will greatly reduce the amount of sediment and other pollutants washing off-site.
- Use stone “check dams” to slow stormwater and allow sediments and other pollutants to settle out before running off-site.
- Cover outdoor storage piles and materials to prevent contact with stormwater.
- Push and dump snow in areas away from surface waters. Snow piles often contain large amounts of sand, sediment, and trash which need to be properly managed once the snow melts.

SUMMARY OF IMPORTANT POINTS

- Know whether your wastewater discharges are going to a municipal wastewater treatment plant, an on-site septic system, or being discharged to the ground.
- Make sure you have permission from your local wastewater treatment plant operator for your discharges to the local sewer system.
- Managing stormwater runoff from your property is your responsibility.

Air Pollution

Air pollution can be defined simply as the presence of any air contaminant in the outdoor air that may cause harm or interfere with the enjoyment of life. Air pollution can come from natural sources (forest fires, volcanic eruptions) and man-made sources and includes contaminants such as dust, fumes, exhaust, chemicals and smoke.

Vehicle service and maintenance facilities encompass a wide variety of operations that can cause air pollution, including:

Cleaning solvents

Petroleum-based solvents used for parts cleaning and other solvents found in aerosol cleaners are volatile organic compounds (VOCs) which are a key ingredient in the formation of smog and may also be of concern due to their toxicity.

Air conditioning systems

Older vehicles may still contain CFC-12 (Freon) which results in destruction of the earth's ozone layer when released to the environment. While the substitute refrigerant, HFC134-a, does not destroy the ozone layer, it is considered a greenhouse gas and thus contributes to global warming.

The U.S. EPA regulates how CFCs are handled from motor vehicle air conditioners. Federal law prohibits the venting of any refrigerants into the atmosphere and requires shops that repair, service or replace air conditioning systems to capture and recycle refrigerants. Technicians who service motor vehicles must use EPA-approved equipment and must themselves be trained and certified by an EPA-approved organization. For more information, see FACT SHEET - FS12 "Motor Vehicle Air Conditioning."



The U.S. EPA's Stratospheric Ozone Protection Program can be reached at 800-296-1996 or visit their website by searching key words 'EPA Air Conditioning.'

Space Heating

Wood, oil (including used oil), and to a lesser extent natural gas/propane fired space heaters, boilers and furnaces generate air pollution. Some fuels release less air pollutants than others but any heating system requires attention to ensure proper combustion and to minimize smoke and other pollution. An annual cleaning and tune-up is a proven method for ensuring the efficient operation of space heating equipment. Outdoor wood-fired units in particular have been found to be grossly inefficient and polluting.

Road Dust

Road dust from unpaved traffic areas and parking lots – Road dust acts as a respiratory irritant and may result in a public nuisance. Dust suppressants such as calcium chloride may be applied as necessary as a best management practice to prevent dust.

Welding

Fumes and other pollutants including toxic heavy metals are released during welding operations.

Gasoline Vapors

Particularly where gasoline is stored on-site, vapors are released in the absence of controls during tank and vehicle refueling. Gasoline and its vapors contain a mix of VOCs, many of which are highly toxic. In addition to refueling operations, vapors are released from minor spills, leaks or open containers indoors that can result in unhealthy worker exposures.

Autobody Work & Spray Painting

The pollutants of concern associated with autobody repair include: particulate matter in the form of sanding and/or sandblasting dust and coating overspray, strong odors from solvents contained in coatings and cleaning solvents, and volatile organic compounds (VOCs) and hazardous air contaminants (HACs), also contained in coating materials and cleaning solvents. To control adverse impacts from these pollutants, facilities are required to comply with 2009 federal regulations on “Paint Stripping and Miscellaneous Surface Coating Operations,” referred to as “The 6H Rule.”

Briefly, the 6H Rule targets any spray-applied coatings containing compounds of cadmium (Cd), chromium (Cr), lead (Pb), manganese (Mn) and nickel (Ni), all classified as Hazardous Air Pollutants.



For more information on the 6H Rule, call us at the Environmental Assistance Office at 800-974-9559. We would be happy to send you a copy of our *2014 Autobody Repair Technician’s Guide to Vermont’s Environmental Regulations*. The Guide can also be viewed at our website searching key words ‘Vermont Autobody Guide.’

You may also want to visit U.S. EPA’s website by searching key words ‘EPA 6H Rule.’

VERMONT AIR POLLUTION CONTROL REGULATIONS

In general, the combined air emissions from individual vehicle service and maintenance facilities are relatively low and do not require a permit from the Department of Environmental

Conservation’s Air Quality and Climate Division. Still, the emissions are a concern for the general public as well as worker exposure. Thus, the APC Regulations require the taking of “reasonable precautions” to limit excessive smoke, odors, dust or other air pollutants so as to avoid causing a nuisance to the general public.

Where autobody repair and the application of spray-applied coatings is a part of the business, owners and operators need to be aware that the VOCs released to the environment from spray painting and solvents used for cleaning parts to be painted and paint equipment may cause overall air emissions to approach the 5 ton per year threshold for permitting. If autobody work is an important part of your business, you should keep records of all paints, solvents and other VOC-containing materials for three years as an indicator of annual air emissions. Please call the Environmental Assistance Office if you have any questions.

SELF AUDIT CHECKLIST FOR AIR QUALITY

The following checklist summarizes basic air pollution requirements and will help you determine if you are in compliance. The statements are worded such that a “No” response indicates a likely compliance problem.

-
1. The cover on parts cleaning equipment using a petroleum-based solvent is kept closed when not in use or when parts are left to soak.

Yes No N/A



See [FACT SHEET - FS16: “Petroleum-Based Parts Cleaning.”](#)

-
2. The emission control system, including catalytic converter and gas cap, are visually inspected, and on-board diagnostics are checked electronically (for all 1996 and newer vehicles), when performing an annual Vehicle Inspection.

NOTE: *Improperly working emission control systems must be repaired.*

Yes No N/A

-
3. If burning used oil for space heating, only oil that meets “specification” is burned in approved equipment, and the combined maximum operating heat input of all used oil burning equipment at the facility does not exceed 500,000 BTU per hour.

Yes No N/A



See FACT SHEET - FS3 “Burning Used Oil Fuel” for information on what constitutes “specification” used oil and other requirements. Approval by the Air Quality and Climate Division is required if burning off-specification used oil or if the aggregate operating heat input of space heating equipment for specification used oil exceeds 500,000 BTU per hour.

4. Technicians performing service on air conditioning systems have been certified to work with refrigerants and are using approved equipment.

Yes No N/A



See FACT SHEET - FS12 “Motor Vehicle Air Conditioning” for more information on required procedures affecting refrigerant recovery and reuse.

5. If autobody repair and spray painting are part of your operations, the facility maintains three years of purchase records for any VOC-containing materials and is in compliance with the federal “6H” regulation on “Paint Stripping and Miscellaneous Surface Coating Operations.”

Yes No N/A



Consult the Air Pollution checklist in EAO’s 2014 “*Autobody Repair Technician’s Guide*.” for more information on 6H and recordkeeping associated with the use of VOC-containing materials. Your paint supplier may be a good source of information as to whether any of the 6H metals are present in any of the coatings that you are spraying.



SUMMARY OF IMPORTANT POINTS

- Cover parts washers using petroleum solvents when not in use.
- Be aware of dust, smoke or odors leaving your facility that might create a “public nuisance.”

Petroleum Storage

UNDERGROUND STORAGE TANKS

An Underground Storage Tank (UST) is any tank, including connected underground piping, the volume of which is 10% or more beneath the surface of the ground AND which is or has been used to store liquid petroleum. This includes but is not limited to gasoline, diesel fuel, hydraulic fluid, used oil and heating oil, but *not* LP gas. However, USTs used for heating oil that are *exclusively* for on-site heating do not need a permit and thus are subject to considerably less regulatory oversight, except for used oil heating USTs.

Oil/water separators are not USTs (see FACT SHEET - FS15: "Oil/Water Separators"), nor are underground tanks used to store hydraulic fluid for car lifts.

The objectives of the UST Program are to ensure that:

- UST systems are properly constructed and designed using recognized industry standards;
- Installations and repairs are conducted and inspected by qualified individuals;
- Active USTs are properly operated and monitored for releases;
- Upon closure, USTs are properly decommissioned and sites assessed for contamination.

Self Audit Checklist for USTs

The following checklist will help you determine if you are in compliance with UST regulations. The statements are worded such that a "No" response indicates a potential compliance issue.

-
1. The UST has been registered with the DEC's UST Program.

Yes No N/A



Registration forms are available online. Search key words 'Vermont UST Permit.' Registrations are forwarded to the town in which the UST(s) is located to be recorded in the municipal land records. If ownership of an UST changes, the new owner must register within 30 days of transfer.

-
2. The UST has an operating permit issued by the UST Program.

Yes No N/A

i **EXCEPTION:** An UST storing heating oil that is not used oil and that is used exclusively for on-premises heating (including domestic hot water) is not required to be permitted, regardless of size.

i Operating permits are typically issued for a five year period. There is an annual permit fee of \$100/UST.

i It is through permitting that requirements for UST materials of construction, leak detection, corrosion protection, recordkeeping, etc. are implemented. For more information search key words 'Vermont UST Maintenance.'

3. An annual inspection of any permitted UST for compliance with the regulations has been performed and the self-certification form submitted to the UST Program.

Yes No N/A

i Forms to self certify compliance are found online at search key words 'Vermont UST Program.' Forms may be filled out on-line and must be submitted by December 31st of each year.

4. The facility has a designated Class A, B and C operator for any permitted UST(s).

Yes No N/A

i For information on the UST operator training and certification requirement search key words 'Vermont UST Operator Training.'

5. For new and replacement USTs, a permit has been obtained from the UST Program prior to the commencement of construction.

Yes No N/A

i Construction permits are issued for one year. The DEC has funds available to make zero interest loans of up to \$150,000 for the removal, replacement or upgrade of an UST (or aboveground storage tank). Contact the UST Program for more information.

6. Any suspected release of petroleum from an UST is reported to the UST Program within 24 hours of discovery (unless it is determined that leak detection systems are not working properly. Defective leak detection systems must be repaired within 72 hours).

Yes No N/A



Any confirmed release of petroleum of 2 gallons or more must be reported as soon as possible to the UST Program at 802-828-1138 during normal working hours, or by calling the 24-hour Vermont Hazardous Materials Reporting Hotline at 800-641-5005.

-
7. For permanent closure of an UST, the UST Program has been notified at least 5 business days prior to the scheduled closure date.

Yes No N/A



An UST which has not been used for a period of one year or more must be removed from the ground, unless permission is granted by the UST Program to close the tank “in-place.” A site assessment for contamination is required for all UST closures.

ABOVEGROUND STORAGE TANKS (AST)

The Vermont Department of Public Safety, Division of Fire Safety, administers construction standards for ASTs used for the storage of flammable and combustible liquids. New and replacement ASTs used for petroleum, including liquefied petroleum (LP) tanks, must obtain a permit. The Division of Fire Safety oversees these requirements out of its Regional Offices located in Williston, Barre, Rutland and Springfield.

The Department of Environmental Conservation’s Waste Management Division also administers regulations affecting the storage of liquid petroleum (not including LP gas) in ASTs. These regulations generally impose additional standards for new installations as well as clarify reporting and response measures to be taken in the event of a release of petroleum. DEC’s AST regulations *do not require a permit*. The regulations include operating guidelines for existing ASTs. They can be viewed online by searching key words ‘Vermont Aboveground Storage Tanks.’

Self Audit Checklist for ASTs

The following checklist will help you determine if you are in compliance with AST regulations. The statements are worded such that a “No” response indicates a potential compliance issue.

-
1. For any new or replacement AST used for the storage of a flammable or combustible liquid, a construction permit has been obtained from the appropriate Regional Office of the Division of Fire Safety.

Yes No N/A



The application form for a construction permit can be found online by searching key words 'VT Fire Safety Construction.'

2. For any new or replacement AST used for the storage of heating fuel, motor fuel or used oil, design and installation standards conform with the requirements of Subchapter 3 of the DEC's Aboveground Storage Tank Rules.

Yes No N/A



The AST Rules can be viewed online by searching key words 'Vermont Storage Tanks.'

3. Any confirmed release of 2 gallons or more of petroleum from an AST to the environment is reported to DEC's Waste Management and Prevention Division as soon as possible.

Yes No N/A



Call 802-828-1138 during normal working hours, or the 24-hour Vermont Hazardous Materials Reporting Hotline at 800-641-5005 to report a release.



Reasons to report a suspected release include an unusual loss of product, strong petroleum vapors in the vicinity or other environmental conditions that suggest a release may have occurred.

4. The total *capacity* of all aboveground petroleum storage at the facility (include ASTs and any container 55 gallons or greater) exceeds 1320 gallons and thus a Spill Prevention, Control and Countermeasure (SPCC) Plan has been prepared.

Yes No N/A



SPCC requirements are administered by the U.S. EPA. See FACT SHEET - FS20 "Federal Spill Prevention, Control, and Countermeasure Regulation" for more information. Call the DEC Environmental Assistance Office for more information and help in putting together a SPCC Plan.

5. Any AST that is used to store *used oil* is labeled with the words "Used Oil" and equipped with secondary containment if it is located out-doors.

Yes No N/A



See FACT SHEET - FS22 "Used Oil" for more information.

6. Any AST used to store gasoline is a UL-approved, 2 hour fire-resistant tank equipped with secondary containment?

- Yes No N/A



Contact the Regional Office of the Division of Fire Safety serving your town for more information.

7. Any AST which is out-of-service for more than one year is either properly disposed of OR inspected and found to be in sound condition.

- Yes No N/A



DEC's AST regulations (section 9-307) address closure procedures, including inspection and testing requirements related to returning an AST to service.



SUMMARY OF IMPORTANT POINTS

- Register your UST with the DEC's UST Program.
- The above-ground storage of petroleum in ASTs is subject to two and perhaps three jurisdictions. The Department of Public Safety, Division of Fire Safety regulates the storage of flammable and combustible liquids and issues construction permits for new ASTs. The DEC's Waste Management Division administers standards for new and existing ASTs but no permit is required. The U.S. EPA Region 1 oversees the Spill Prevention, Control and Countermeasure Program (SPCC) when total aboveground storage capacity for petroleum is 1320 gallons or more.

Fact Sheets

FACT SHEETS

FS1	Aqueous Parts Cleaning.....	30
FS2	Asbestos Containing Auto Parts	33
FS3	Burning Used Oil Fuel.....	36
FS4	Hazardous Material Spill Response	39
FS5	Making a Hazardous Waste Determination.....	42
FS6	Materials Banned From Vermont Landfills	45
FS7	Lead-Acid Batteries	47
FS8	Managing Air Bags	49
FS9	Managing Automotive Antifreeze	52
FS10	Managing Waste Fuel and Fuel/Water Mixtures.....	55
FS11	Mercury Containing Lamps & Auto Switches	57
FS12	Motor Vehicle Air Conditioning	60
FS13	Oil Filters	62
FS14	Oily Wastes	64
FS15	Oil/Water Separators	67
FS16	Petroleum-Based Parts Cleaning	69
FS17	Scrap Metal, Recycling, and Landfill Disposal Bans	72
FS18	Scrap Tires.....	74
FS19	Shop Rags Contaminated with Used Oil or Hazardous Waste	76
FS20	Federal Spill Prevention, Control, and Countermeasure Regulation	79
FS21	Universal Waste.....	81
FS22	Used Oil.....	83
FS23	Washwater Discharges From Vehicle Washing	86
FS24	Waste Motor Vehicle Fuel and System Components	88

Aqueous Parts Cleaning

This Fact Sheet covers aqueous solutions used in parts cleaning equipment such as enclosed spray washers, sinks, and dip tanks to remove oil, grease and other solid materials. A separate FACT SHEET - FS16 "Petroleum-Based Parts Cleaning," covers parts washers that use solvents such as mineral spirits and naphtha.

What are some of the advantages associated with aqueous parts cleaning?

Aqueous cleaners are water-based solutions that do not contain hazardous volatile organic compounds (VOCs) and, unlike many petroleum-based solvents, are non-flammable. Instead of chemically dissolving oil and grease, they rely on heat, agitation and detergents to remove these contaminants from parts. Aqueous cleaners are less toxic than petroleum-based solvents and therefore are safer for employees to use.

To extend the life of cleaning solutions, the better aqueous systems are designed to remove oils and solids using skimmers and filters. In fact, cleaning solutions can last indefinitely if they are properly maintained. In all cases though, it is necessary to periodically add water and detergent formulations due to loss through evaporation, filtration and by being carried out on parts.

What is a microbial cleaner?

These are aqueous cleaning solutions typically used in conjunction with parts cleaning sinks that extend cleaner life by relying on microscopic organisms to consume oil, grease, and other organic contaminants. Like other aqueous cleaning solutions, they perform best when heated. Solids need to be removed through filtration or other means and equipment manufacturers offer various recommendations for doing this.

How is spent aqueous parts cleaning solution regulated?

Because spent aqueous solution is likely contaminated with oil, grease, and possibly metals like lead or chromium, there are environmental concerns associated with its disposal. Depending on the level of contamination, spent aqueous solutions may be regulated as hazardous waste. If approved for discharge, such solutions must be managed according to Vermont wastewater requirements.

What are the basic wastewater requirements?

Spent aqueous cleaning solutions that are non-hazardous may be discharged to a municipal wastewater treatment plant provided the business has received permission from both the municipality

(treatment plant operator or other official) and the Department of Environmental Conservation's Watershed Management Division. Be prepared to inform the plant operator about the volume of spent solution to be discharged, the pH and the contaminants likely to be present. If testing is necessary, take a sample of the wastewater near the end of its useful life.

Aqueous cleaning solutions should never be discharged to an on-site septic system since contaminants of concern are not treated in the soil environment and can result in groundwater contamination.

How are oils and solids removed from parts washers regulated?

Oils that are skimmed, filtered or otherwise removed from aqueous parts washers are subject to regulation either as "used oil" (refer to FACT SHEET - FS22 "Used Oil" for more information) or as hazardous waste under the Vermont Hazardous Waste Management Regulations. Oil that is managed as hazardous waste is identified by the VT02 hazardous waste code (i.e., wastes containing greater than 5% petroleum distillate).

Sediment and other solid materials that are removed from aqueous parts washers are regulated as solid or hazardous waste. Although these wastes generally do not meet hazardous waste criteria, any business generating this material is responsible for making a determination, based either on laboratory testing or his or her knowledge of the material (refer to FACT SHEET - FS5 "Making a Hazardous Waste Determination" for more information). Non-hazardous solids may be disposed of in the regular trash.

What contaminants should be tested for?

If a business decides that laboratory testing is necessary, it should only test for those contaminants likely to be present in the waste in order to keep the cost down. A "total metals" analysis can be used to screen for the specific metals of concern (i.e., lead, chromium or other regulated metal), and a "total petroleum hydrocarbon" (TPH) test can be used to determine the concentration of oil in the spent material. Samples of aqueous cleaning solutions to be sent for laboratory analysis should be taken near the end of the solution's useful life. Call Hazardous Waste Program staff (802-828-1138) or the non-regulatory Environmental Assistance Office (800-974-9559) for help in deciding what to test for and how to interpret results.

Can wastewater be evaporated?

Wastewater from an aqueous parts cleaning system may be evaporated provided:

- It is non-hazardous OR hazardous waste only because it contains greater than 5% by weight petroleum distillate material;
- Evaporation equipment has been approved by Vermont's Air Pollution Control Division (this is generally straight-forward and does not require a permit for pre-engineered systems); and
- Oily residue remaining after evaporation is managed either as "used oil" or as hazardous waste.



BEST MANAGEMENT PRACTICES

- Install cleaning equipment that uses water efficiently or is capable of recycling water.
- Remove heavy soils from parts with a scraper or rag before aqueous cleaning to reduce cleaning time, water usage, and the amount of contamination introduced into the cleaning solution.
- Conduct cleaning operations on an impervious surface.

Asbestos Containing Auto Parts

This Fact Sheet covers management options for businesses that handle auto parts that potentially contain asbestos, such as brake linings and clutch facings. Although major auto manufacturers no longer use asbestos parts in new vehicles, aftermarket parts containing asbestos are still being made, imported to the United States and used in repairs. This, in conjunction with the presence of asbestos containing parts on older cars, should cause auto repair shops to take precautions where circumstances could lead to employee exposure.

What is Asbestos and Why is it a Concern?

Asbestos is the name given to a number of naturally occurring fibrous silicate minerals that have been mined for their useful properties such as thermal insulation, chemical and thermal stability, and high tensile strength. Asbestos is made up of microscopic bundles of fibers that may become airborne when disturbed. These fibers get into the air and are inhaled into the lungs, where they may cause significant health problems.

Researchers still have not determined a “safe level” of exposure, but know greater and longer exposure increases the risk of contracting an asbestos related disease. Health effects can result from even a single exposure. Some of these health problems include asbestosis (scarring of the lung tissue), mesothelioma (a type of fatal cancer of the lining of the chest), and lung, intestinal and voice box cancers. It may take 15 to 30 years for these health problems to show up after exposure. Because health effects are not immediate, mechanics and supervisors may develop a false sense of security without realizing that disease may develop much later. Thousands of auto workers are diagnosed each year with asbestos-related diseases. Few mechanics take protective measures when working with brakes - mainly, they say, because they believe asbestos is no longer present.

When is Asbestos Exposure a Problem for Vehicle Service Providers?

Millions of asbestos fibers can be released during brake and clutch servicing. Grinding and beveling friction products can cause even higher exposures. Asbestos released into the air lingers long after a brake job is done and can be breathed in by everyone inside a garage, including customers. Mechanics can expose their families when asbestos is carried on work clothing into their family cars and homes. Eating, drinking and smoking should not be done in an area where brake work is done. Mechanics should wash their hands & face before eating. They should also wash exposed skin and change clothes before going home.

Unless a mechanic is certain before brake work starts that a vehicle's brakes are not lined with asbestos, it should be assumed for the sake of caution that asbestos is present.

If Brakes Are Lined With Asbestos, Which Brake Cleaning Methods Release Asbestos Fibers Into the Air?

The following brake cleaning techniques can result in the release of asbestos into the air and consequently may lead to employee exposure:

- Using a compressed air hose to clean drum brakes;
- Wiping with a dry rag or brushing dust from the assembly;
- Wiping with a wet rag or brush – asbestos will still scatter even if the rag or brush is wet. Furthermore, once dry, the rag or brush can spread the fibers around the work area;

Which Brake Cleaning Methods Release Asbestos Fibers Into the Air?

- Using liquid squirt bottles or solvent sprays;
- Using a water hose;
- Using a shop vacuum cleaner – a shop vacuum filter is not fine enough to collect asbestos fibers.

What is the Best Way to Minimize Asbestos Exposure?

Whenever possible, use pre-ground, installation-ready brake linings and clutch facings. In situations where asbestos exposures cannot be eliminated entirely, they should be reduced to the lowest possible level. To accomplish this, consider:

- Using specially designed “wet collection” equipment. This is generally a portable sink (which sits on a reservoir typically containing an aqueous brake cleaning solution) which can be rolled directly under the area to be cleaned. Using low pressure flow, the unit pumps the solution over the brake assembly, while the resulting wash is collected in the sink (often with adjustable height) and flows back into the reservoir after being filtered. The filtered solution is then reused for additional cleaning.
- Using enclosure equipment with a HEPA (High-Efficiency, Particulate Air filter) vacuum cleaner for brake cleaning. Enclosure equipment for clutch repair is under development.
- Where friction materials containing asbestos must be machined, beveled, or lathe-turned, adequate local exhaust ventilation equipment connected to a HEPA vacuum collector should be used. Such equipment should be designed and set up by a professional ventilation engineer, using specifications such as those proposed the American Conference of Governmental Industrial Hygienists. A comprehensive asbestos control and monitoring program must be developed where machining, beveling, or lathe-turning of asbestos parts is done.
- Respirators with asbestos-compatible cartridges may be appropriate for secondary protection during activities where employees have a greater risk of exposure; however, because uncontained brake and clutch repair could contaminate an entire garage with asbestos fibers, mechanics and other employees would have to wear a respirator all day to be fully protected. Please note that respirator use requires a respiratory protection program, including worker training, medical monitoring, proper respirator selection and maintenance, fit testing, and periodic inspections.

How Should Asbestos Containing Auto Parts be Disposed?

Asbestos disposal is covered under Vermont's Solid Waste Management Rules. Although asbestos materials are not banned from disposal in Vermont, the solid waste landfills operating in the State are no longer accepting asbestos waste. Because of this, vehicle service facilities that generate asbestos containing waste auto parts must have a Vermont Department of Health certified asbestos contractor pick up the asbestos containing waste for proper disposal. The asbestos containing waste auto parts need to be properly packaged prior to shipment by double-wrapping the waste in polyethylene sheeting (with total thickness of 6 mills or greater) and secured with tape. The polyethylene sheeting must fully encapsulate the asbestos containing waste and be secured for transport in appropriate containers. The containers must be transported directly to a disposal facility, and not mixed with other waste types or compacted.

How Should Asbestos Containing Auto Parts be Disposed?

Asbestos-containing waste must be clearly labeled as follows:

CAUTION

CONTAINS ASBESTOS FIBERS

AVOID CREATING DUST

CANCER AND LUNG DISEASE HAZARD

Burning Used Oil Fuel

In Vermont, used oil may be burned as fuel provided certain requirements are met. These requirements are found in Subchapter 8 of the Vermont Hazardous Waste Management Regulations (VHWMR), and Section 5-221(2) of the Air Pollution Control Regulations (APCR). While the APCR only cover “waste oil” burning, Subchapter 8 of the VHWMR establishes standards for all aspects of used oil management (i.e., storage, transportation, marketing and burning).

This Fact Sheet only summarizes the requirements applicable to burning “specification” used oil fuel in “small fuel burning equipment” (i.e., space heating equipment designed specifically for burning used oil fuel), an activity that is exempt from the APCR. Burning used oil fuel in larger equipment, or burning off-specification used oil, is subject to regulation under the APCR and more stringent VHWMR requirements.

TABLE 1 – USED OIL FUEL SPECIFICATIONS	
Constituent/Property	Allowable Level
Arsenic	5 ppm maximum
Cadmium	2 ppm maximum
Chromium	10 ppm maximum
Lead	100 ppm maximum
Flash Point	100 °F minimum
Total Halogens	1000 ppm maximum
PCBs	< 2 ppm maximum
Net Heat of Combustion	8000 BTU/lb minimum

This Fact Sheet also presumes that when used oil fuel is received by a burner from off-site, the oil is shipped in amounts that do not exceed 55 gallons at one time. When used oil is shipped in amounts greater than 55 gallons, more stringent VHWMR requirements apply to the facilities that ship, transport and receive the oil.

General used oil management requirements are summarized in the FACT SHEET - FS22 “Used Oil.”

What is specification used oil fuel?

Specification used oil fuel meets the “allowable” constituent and property levels identified in Table 1 of VHWMR Section 7-812.

What is small fuel burning equipment and how is it regulated?

The term “small fuel burning equipment” refers to all used oil burning equipment at a facility when the *maximum operating heat input* for that equipment is equal to or less than 500,000 BTU/hr. Small fuel burning equipment is exempt from the permitting requirements of the Vermont Air Pollution Control Regulations, but still must meet the basic standards described in this Fact Sheet. Facilities with used oil burning equipment that exceeds the 500,000 BTU/hr heat input threshold may be required to obtain a permit and should contact the Vermont Air Pollution Control Division. For example, a facility operating two used oil burners, each with operating heat input values of 300,000 BTU/hr, may need to obtain a permit because collectively the equipment has a maximum operating heat input value of 600,000 BTU/hr.

Burning used oil fuel in this type of space heating equipment is allowed provided:

- Combustion gases are vented to ambient (outdoor) air;
- Stacks are not equipped with devices that would impede the upward discharge of the exhaust gases (i.e., no raincaps);
- No more than one space heater is connected to an above-ground storage tank; and
- The unit is operated with no visible smoke (except as allowed under Section 5-211 of the APCR).

Can any type of used oil be burned in small fuel burning equipment?

The types of used oil that may be burned in small fuel burning equipment are limited to vehicle crankcase and machine gearbox oil. Other types of used oil (e.g., hydraulic fluids, compressor oils, petroleum-based power steering and transmission fluids, metal working fluids) may be burned as fuel only after approval is granted by the Waste Management Division. Approval is based on product information provided on the Safety Data Sheet (SDS) and a description of the process generating the used oil.

Does used oil fuel need to be tested for all the Table 1 constituents?

- Business that either burn their own used oil on-site, or burn used oil received from off-site in shipments of less than or equal to 55 gallons:
 - Must only test the used oil (from each source) for total halogens. A field screening test kit may be used to determine if the 1,000 ppm specification limit is met for total halogens. Contact the Waste Management Division or Environmental Assistance Office for information about field screening test kits and how to obtain them.
 - If there is reason to believe that any of the remaining Table 1 specifications (i.e., those specifications other than total halogens) would not be met by a volume of used oil, that oil must be tested for the suspected constituents or properties.
- Businesses that receive used oil fuel in shipments greater than 55 gallons:
 - Must establish that the used oil fuel meets all of the Table 1 specifications; this testing may be conducted by either the burner or the used oil generator.

How often do I have to test used oil fuel?

Used oil fuel from a specific source must be tested one time. The oil must be retested only if there is reason to believe that the quality of the oil, or the process generating the oil, has changed such that

the Table 1 specifications would not be met. A burner does not need to test used oil fuel received from off-site if the oil has already been tested by the generator (or transporter) and found to meet Table 1 specifications.

Do I need a permit to burn used oil fuel in small fuel burning equipment?

No permit is required to burn specification used oil. However, any business that accepts used oil from off-site, or that generates hazardous waste (e.g., oily sorbent or debris), does need to notify the Waste Management Division of its used oil collection or hazardous waste activity using the **VERMONT HAZARDOUS WASTE HANDLER SITE ID FORM** (available on-line or from the Waste Management & Prevention Division). Businesses that *only burn used oil generated on-site*, and that do not generate any hazardous waste, are not required to notify.

Can I burn used oil fuel that I don't generate?

Yes. In addition to burning used oil fuel that is generated on-site, burners may accept crankcase and machine gearbox oil from the following sources:

- Do-it-yourselfers (households that generate used oil);
- Off-site facilities that are owned and operated by the burner; or
- Other businesses and municipalities.

What do I need to do if I accept used oil fuel from off-site?

- When used oil fuel is received in shipments of no more than 55 gallons from do-it-yourselfers or other businesses/municipalities, notify the Waste Management Division (using the **VERMONT HAZARDOUS WASTE HANDLER SITE ID FORM**) of status as a “used oil collection facility.”
- Facilities that receive used oil in shipments larger than 55 gallons are subject to more stringent “transfer facility” standards (40 CFR § 279.40). Facilities initiating shipments of more than 55 gallons of used oil fuel may be subject to the VHWMR § 7-809 “marketer” standards.
- Maintain records of used oil fuel accepted from other businesses and municipalities documenting:
 - the quantity of used oil accepted;
 - specification testing results;
 - the name, address, telephone number and EPA identification number of any business or municipality from which used oil fuel is accepted; and
 - the name, address and EPA identification number of the transporter (if applicable).
- These records must be retained for at least three years.
- Store used oil fuel in containers, above-ground tanks, or underground storage tanks as required under Subchapter 8 of the VHWMR (refer to the FACT SHEET - FS22 “Used Oil” for more information).

Hazardous Material Spill Response

Who should read this Fact Sheet?

This Fact Sheet applies to any Vermont business or municipality that handles hazardous material (including hazardous waste, petroleum products, or CERCLA hazardous substances), and consequently may need to respond to a release of hazardous material (spill) to the environment. It summarizes the spill response requirements included under Section 7-105 in the Vermont Hazardous Waste Management Regulations (VHWMR) and describes response procedures for spills that occur at fixed facilities and during transportation.

How do I respond to a spill at a fixed facility?

1. Assess the Hazard and Perform Initial Response (if appropriate)

For spills that can be safely managed without assistance:

- Stop the spill at its source;
- Prevent spilled material from entering storm drains, waterways, drainage ditches, etc.; and
- Contain spilled material using a barrier (absorbent pads or socks), temporary dike or trench.

For all other spills, a cleanup contractor will likely need to be hired since they have the training and equipment necessary to safely respond to dangerous hazardous material spills. A list of spill cleanup contractors that operate in Vermont is maintained on-line.

2. Report the Spill

Any hazardous material spill to the land or water that meets the following criteria must be immediately reported to the Department of Environmental Conservation (DEC) Spill Response Team (spill team) by calling the **24-HOUR HAZARDOUS MATERIALS SPILLS HOTLINE AT 800-641-5005**. *If there is any question about whether a spill is reportable, call.*

- A spill of 2 gallons or more;
- A spill that is less than 2 gallons, but poses a threat to human health or the environment (e.g., a gallon of gasoline spilled to a wetland); or
- A spill that exceeds a CERCLA reportable quantity.

Any person who has knowledge of a spill and who may be subject to liability for that spill, is responsible for reporting the spill. In addition to reporting to the DEC, any spill of hazardous material that impacts (or threatens) surface water (e.g., lakes, streams, wetlands) must also be reported to the U.S. Coast Guard via the National Response Center at **800-424-8802**.

3. Clean up and Follow up

ANY BUSINESS OR MUNICIPALITY WHO MAY BE RESPONSIBLE FOR A SPILL MUST:

- Ensure that the spill is cleaned up to the extent that it no longer presents a threat to human health or the environment;
- Make a hazardous waste determination for all spill cleanup materials;
- Ensure that contaminated soil/water/debris is collected and managed appropriately; and
- **FOR ANY REPORTABLE SPILL, SUBMIT A WRITTEN FOLLOW-UP REPORT WITHIN 10 DAYS DETAILING HOW THE SPILL WAS CLEANED UP AND HOW WASTE WAS MANAGED.**

What happens when a spill is reported to the DEC?

When a spill is reported to the DEC, a spill team member will determine if on-site assistance is necessary to assess environmental impact and/or oversee cleanup efforts. While on the phone, the spill team member can provide assistance related to spill containment and cleanup, and the proper management of cleanup materials. The DEC's spill team can also assist with obtaining information about spilled materials, contacting other individuals with potential cleanup obligations, and, if needed, hiring a cleanup contractor.

It is important to report spills immediately so that the DEC can quickly assess the potential for environmental impact, and coordinate outside assistance as necessary. A delay in reporting can result in greater environmental impact and a more complicated and costly cleanup.

What happens when a hazardous material spill occurs during transportation?

Although the primary obligation of reporting and cleaning-up a hazardous materials spill that occurs during transportation lies with the owner or operator of the vehicle from which the material has been released, transportation related spills usually are reported to the DEC by the emergency responder (fire chief or police officer) who first arrives at the spill scene.

While transportation-related spills are subject to the same reporting requirements as those that occur at fixed facilities, any transportation-related spill that meets the criteria of a "Reportable Incident" specified in Section 171.15 of 49 CFR (the Federal Department of Transportation regulations) must also be reported to the National Response Center at 800-424-8802. Examples of Reportable Incidents include a death or injury requiring hospitalization; closure of a major transportation artery or facility for more than one hour; and evacuation of the general public for more than one hour.

An incident commander (in most cases, the local fire chief) is usually designated to oversee the spill response effort in consultation with the DEC spill team. The responsible party(ies) may also be involved in the cleanup depending on their willingness and/or ability. Follow-up to the initial spill response is generally coordinated between the DEC's spill team and the responsible party(ies).

|||||

WHAT ARE SOME BEST MANAGEMENT PRACTICES FOR SPILL PREVENTION AND EMERGENCY PREPAREDNESS?

- Develop a spill prevention plan; involve employees as they know how and why spills occur.
- When transferring liquids, use drip trays, funnels or other means to avoid spills.
- Use spring-loaded drum covers, valves or other positive shut-off devices.
- Keep all containers closed when not adding or removing material.
- Store all containers on an impervious surface (concrete) that is protected from weather.
- Instruct employees in spill response procedures. Cover basic safety precautions like:
 - Minimize contact with or walking in spilled material
 - Minimize inhalation of any gases, vapors or smoke that result from a spill
 - Promptly wash any skin that comes in contact with spilled material
- Post a list of emergency numbers next to the phone.
- Maintain spill control and containment equipment in a designated area.

Making a Hazardous Waste Determination

What does it mean to make a hazardous waste determination?

This is the procedure used to evaluate whether a waste is regulated as a hazardous waste under the Vermont Hazardous Waste Management Regulations (VHWMR).

Everyone knows that some businesses generate hazardous waste (e.g., dry cleaners, electroplaters, auto body shops). For other businesses, hazardous waste generation may be less obvious. For example, most people do not think of food product manufacturers, educational institutions, and retail stores as producing hazardous waste. Upon closer examination, however, these businesses may discover that hazardous wastes are generated through grounds-keeping, painting, vehicle maintenance and other activities.

Who is responsible for making a hazardous waste determination?

Any business, municipality or other organization that generates a waste must determine if that waste is a hazardous waste. While household waste is exempt from regulation, waste generated by a business operating out of a home is not.

What wastes need to be evaluated?

All waste must be evaluated to determine if it is a hazardous waste. However, if a material is not usable by one entity, but can legitimately be used as is (i.e., without first being recycled, filtered or otherwise processed in any way) by another, the material is *not* considered to be a waste and therefore does not have to be evaluated.

A good way to start is by preparing an inventory of all wastes generated at your facility. Be sure to include:

- Process wastes, manufacturing by-products, and spent laboratory chemicals
- Maintenance wastes like oily sorbents, spent fluorescent lamps and parts washing solvent (even if the unit is maintained by another company)
- Out-dated or otherwise un-needed chemicals or raw materials
- Spill clean-up materials, emission control residues and boiler blow-down water

How is a hazardous waste determination made?

Step 1: See if the waste is exempt from regulation as a hazardous waste. Section 7-203 of the VHWMR includes exemptions for certain wastes so long as specific management conditions are met. Section 7-204 includes additional exemptions that are conditioned upon the waste being reused or recycled.

MAKING A HAZARDOUS WASTE DETERMINATION - FS5

Examples of exempt wastes include: oil filters, lead-acid batteries, antifreeze and “universal wastes” (e.g., fluorescent lamps, cathode ray tubes and mercury-containing devices).

Step 2: If a waste is not exempt, determine if it is a “listed” hazardous waste (i.e., the waste is found on one of five lists in the VHWMR and is assigned a “VT,” “F,” “K,” “P,” or “U” code*). In Vermont, “VT” and “F” wastes are far more common than other listed wastes.

- **VERMONT-LISTED WASTES** (see VHWMR Section 7-211). Vermont regulates six specific wastes that are not regulated under the federal hazardous waste program. An example is oily waste that contains > 5% by weight petroleum distillates – assigned the VT02 code.
- **F-LISTED WASTES** (see VHWMR Section 7-210) are “wastes from non-specific sources.” There are 28 such wastes. An example is “spent non-halogenated solvent,” like acetone – assigned the F003 code.
- **K-LISTED WASTES** (see VHWMR Appendix I) are “wastes from specific sources.” An example is “distillation bottoms from aniline production” – assigned the K083 code – and like most K-listed wastes, is rarely, if ever, generated in Vermont.
- **P-LISTED WASTES** (see VHWMR Appendix IV) These “acutely hazardous wastes” have more protective standards. An example is “sodium cyanide” – assigned the P106 code.
- **U-LISTED WASTES** (see VHWMR Appendix III) These are specific “discarded commercial chemical products or off-specification batches of commercial chemical products.” An example is “methanol” that has never been used and is no longer needed – assigned the U154 code.

Step 3: If the waste is not listed, the generator must then determine if it exhibits any one of four hazardous waste “characteristics” (i.e., ignitability, corrosivity, reactivity and/or toxicity and is assigned a “D” code*).

- **IGNITABLE WASTE** (see VHWMR section 7-205) is liquid with a flash point of less than ~140° F; or is not a liquid and is capable under standard temperature and pressure of causing fire and creating a burning hazard; or is an ignitable compressed gas. Ignitable waste is assigned the D001 waste code.
- **CORROSIVE WASTE** (see VHWMR section 7-206) is liquid with a pH <2 or ≥ 12.5; examples are battery acid and caustic drain cleaner. Corrosive waste is assigned the D002 code.
NOTE: *Corrosive solids are regulated under “Vermont-listed wastes” and are identified by the VT20 code.*
- **REACTIVE WASTE** (see VHWMR section 7-207) may have any of the following properties: is normally unstable; reacts violently with water, forms a potentially explosive mixture with water or can generate toxic gases when in contact with water; or is capable of detonation. Examples are picric acid and dynamite (munitions). Reactive waste is assigned the D003 code.
- **TOXICITY CHARACTERISTIC WASTES** (see VHWMR section 7-208) are wastes capable of leaching any one of 40 specific contaminants in excess of “regulatory levels” when tested in a laboratory using the Toxicity Characteristic Leaching Procedure (TCLP). Toxicity characteristic wastes are assigned the D004 through D043 codes.

How do you determine if a waste meets a listing or exhibits a characteristic?

A generator can use either his or her **KNOWLEDGE OF THE PROCESS** that produces the waste or **ANALYTICAL TESTING**. A generator may assume that a waste exhibits a characteristic without knowing

if it actually meets the criteria for ignitability, corrosivity, reactivity or whether the concentration of suspected toxicity characteristic contaminants actually exceeds regulatory levels.

How does one use process knowledge?

In order for a generator to use process knowledge, sufficient information (such as that provided on labels or Safety Data Sheets) must be available for all materials used in the process or that otherwise contribute to the waste. Be aware, however, that such information only represents raw materials and may not accurately represent what's in the waste. This is especially relevant when it comes to determining if the regulatory level for a toxicity characteristic constituent is exceeded. Generators that rely on process knowledge to make a hazardous waste determination must be able to demonstrate the basis for their claim.

What about analytical testing?

If sufficient information is not available to make a hazardous waste determination, it may be necessary to have a sample of the waste analyzed by a laboratory. Since analytical testing can be expensive, it is important to provide the laboratory with as much information as possible about the waste. For example, if you know that arsenic is the only potentially hazardous contaminant in a waste, there is no need to test for other contaminants. You must keep any test results for at least three years from the date the waste was last sent to a treatment, storage or disposal facility.

How often must a hazardous waste determination be made?

An initial determination must be made on each waste, and the waste must be re-characterized whenever a change is made to the waste-generating process.

Where can I get help in making a hazardous waste determination?

Vermont DEC - Hazardous Waste Management Program Call: 802-828-1138

Vermont DEC - Environmental Assistance Office Call: 800-974-9559

CHEMICAL MANUFACTURERS AND SUPPLIERS Check the Safety Data Sheet (SDS) for any chemical products you use. Your supplier/distributor may be able to assist with questions about their products although they often are not knowledgeable about hazardous waste regulations.

TRADE ASSOCIATIONS Same caveat as above.

** All hazardous wastes are identified by a four-digit "hazardous waste code" that consists of one or two letters followed by two or three numbers (e.g., F005, VT02, D018). The waste codes are used to identify the waste on container labels and other required documents such as the hazardous waste manifest shipping document.*

Materials Banned From Vermont Landfills

The following items are NOT allowed to be landfilled in Vermont and must be properly disposed of through your solid waste district, a permitted waste hauler or during your town-wide waste collection events

This landfill ban applies to commercial business and residential customers.



Mercury-Added Products

Including thermostats, thermometers, manometers, barometers and elemental mercury.



Waste Oil

Including oil filters, unless filters are punctured and hot drained. (See the FACT SHEET - FS13 "Oil Filters".) Please consider recycling your properly drained oil filters with your scrap steel.



White Goods

Including discarded refrigerators, washing machines, clothes driers, ranges, water heaters, dishwashers and freezers.



Untreated Regulated Medical Waste (RMW)

Only treated RMW may be disposed. A certificate of treatment must accompany the treated RMW. RMW generated in the home is not restricted from disposal. See the RMW Regulations for details.

Questions? Contact the Solid Waste Program at 802-828-1138



Paint

Including oil and water based (unless water based is dried and *less than* one gallon), paint thinner, paint remover, stains and varnishes.



Tires



Nickel Cadmium Batteries or Other Rechargeable Batteries

From cordless power tools, video cameras, cellular phones, and personal care items (shavers, etc.).



Lead Acid Batteries



Fluorescent Lamps

Including full-size and compact fluorescents, and high intensity discharge lamps (HID) such as mercury vapor, metal halide, and sodium lamps.



Electronic Wastes (E-Waste)

Including: computer monitors, televisions, telephones, VCRs, DVDs, fax machines, CRTs (cathode ray tubes), printers, keyboards, mice, wireless cell phones, stereo equipment, and much more!



Propane Cylinders

Including one (1) pound (Propane torch size), twenty (20) pound (Grill Size) and larger cylinders.

Not specifically prohibited - but for worker safety reasons, please recycle propane cylinders and keep them out of our landfills.



Liquid Waste

Except household waste, other than septage.

NOTE: Hazardous wastes are also banned from Vermont landfills

Contact your local solid waste management district/alliance or municipality for information about recycling or other waste collection opportunities.

Lead-Acid Batteries

What are Lead-Acid Batteries and why are they of concern?

Lead-acid batteries, which are commonly used in motor vehicles, forklifts, golf carts, garden tractors, and wheelchairs, utilize a sulfuric acid electrolyte solution to convert potential chemical energy to electrical energy. A typical automobile battery contains 18-20 pounds of lead (plates) and 11 pounds of sulfuric acid, and if handled improperly, poses hazards to human health and the environment. Lead is a toxic substance that can contaminate soil and water, while sulfuric acid is corrosive and can cause severe bodily injury upon contact. Lead-acid batteries also present a fire and explosion hazard.

How are Lead-Acid Batteries regulated?

Spent lead-acid batteries that are generated by businesses are regulated as hazardous waste unless they are managed:

1. According to the recycling exemption (discussed below) provided in section 7-204(f) of the Vermont Hazardous Waste Management Regulations (VHWMR); OR
2. As universal waste by following the standards outlined in Subchapter 9 of the VHWMR and Part 273 of the Code of Federal Regulations Title 40 (refer to the FACT SHEET - FS21 "Universal Waste" for more information about this option).

In Vermont, most businesses manage lead-acid batteries under the recycling exemption because state law requires retailers to accept spent lead-acid batteries in return for those that they sell. The law also requires that collected batteries be recycled. Retailers can usually send spent batteries for recycling using the same company that delivers new batteries.

Although household wastes are exempt from the VHWMR, all spent lead-acid batteries, including those generated by households, are *banned from landfill disposal* and should be recycled through a solid waste district or battery retailer.

What conditions must be met to satisfy the recycling exemption?

Spent lead-acid batteries are exempt from regulation as hazardous waste provided:

- Businesses that generate or collect the batteries store them under cover and on an impervious surface;

LEAD-ACID BATTERIES - FS7

- The batteries are transported in accordance with the Federal Department of Transportation requirements (49 CFR 171-177 specifies regulations for packaging, shipping, labeling, and placarding); and
- The batteries are recycled.

BEST MANAGEMENT PRACTICES

- Avoid stockpiling spent lead-acid batteries.
- Check batteries for leaks and cracks prior to storing.
- Store batteries upright to prevent acid leaks through vent holes.
- Keep spent batteries from freezing to avoid cracking their cases.
- Place cracked or leaking batteries in a closed, watertight, acid-resistant storage container such as a five-gallon plastic (polyethylene) pail or bin.
- Store waste battery electrolyte as a corrosive hazardous waste in a compatible container.
- Keep a neutralizing agent, such as baking soda, lime or bicarbonate soda nearby in case acid leaks or spills.
- Place same-size batteries on pallets and separate layers with a shock-absorbing material.
- Stack batteries in layers no more than five high, with the pole side of each battery facing toward the outside of the stack to maximize stability.
- When handling batteries, always wear safety equipment (e.g., gloves, apron, and eye protection) to prevent contact with corrosive materials (sulfuric acid).

Managing Air Bags

What You Need to Know

Passive restraints (air bags or automatic seat belts) are safety devices that automobile manufacturers are required to install in all new vehicles since April 1989. The air bag cartridges or seat belt pretensioner¹ contains a mixture of highly reactive and oxidizing chemical. If the air bag has not been deployed, the material is dangerous to handle. It can explode, it can cause burns if it gets on unprotected skin, and it can severely irritate the lungs if inhaled.

If the air bags have been deployed, the explosion hazard ceases to exist, and you will not have to take special precautions. But many vehicles now contain multiple air bags (side air bags, for example). Any undeployed air bags and pretensioners should be removed from the vehicle before it is sent off to the auto salvage yard for ultimate disposal (that is, for crushing or shredding), or should be removed at the auto salvage yard.

Once you have removed the intact air bag and pretensioner cartridges that are usable, you can send them to a reclamation facility. These are considered to be a recyclable component and will not have to be treated as a hazardous waste. **HOWEVER, IF YOU REMOVE AIR BAGS AND PRETENSIONS AND YOU DO NOT RECLAIM² THEM, YOU MUST HANDLE THEM AS A HAZARDOUS WASTE.**

What can be done to prevent the violent reaction of sodium azide (NaN_3) in undetonated airbags? The airbags must be prevented from going through the automobile-recycling process.

Sodium azide released during the shredding process may contaminate the steel, iron, and nonferrous metals recovered at this stage. Of greater concern, however, is the large amount of heat and friction generated by the shredder. NaN_3 reacts explosively at high temperatures which can cause a greater risk of ignition when airbags pass through the shredder. This danger is amplified if sodium azide comes in contact with heavy metals in the car, such as lead and copper, because these may react to form a volatile explosive.

Regulations

Air bag cartridges that have not been deployed are hazardous waste unless they are reclaimed. Unclaimed air bag cartridges exhibit the hazardous waste characteristic of reactivity (D003) due to the propellant, sodium azide, a highly explosive material. If air bags are reclaimed, they are not considered a hazardous waste.

Store non-deployed air bag units indoors, protected from the weather until they can be resold or disposed of properly. Non-deployed air bags are valuable, so do not deploy them. If the airbag or

pretensioner is defective in any way, it may not be voluntarily triggered. This is considered treatment of a hazardous waste. These items must be managed as hazardous waste and disposed of as such.

If the air bags have been deployed, the material is no longer dangerous (and not hazardous waste), and you will not have to take special precautions. The deployed air bag can then be sent off as a solid waste or shipped with the vehicle hulls to the crusher or shredder.

Employees shipping hazardous materials must be trained and certified in the Federal Department of Transportation rules regarding air bag shipments. For each air bag module and seat-belt pretensioner the shipping paper description must conform to the requirements in 40 CFR 173.166:

http://edocket.access.gpo.gov/cfr_2006/octqtr/pdf/49cfr173.166.pdf

The following BMPs are recommended for the management and recycling of air bags:

- Store non-deployed air bags indoors, protected from the weather until they can be resold.
- If you send air bags, retain shipping papers that indicate the name of the reclaimer, the date of transfer, and the quantity of air bags/cartridges shipped.
- Consider the hazmat training and certification opportunities offered through the Auto Recyclers Association (ARA) at www.airbagresources.com
- Consider following the ARA Protocol for use of “Original Equipment Non-Deployed Airbags” http://a-r-a.org/files/sc_airbagprotocol.pdf
- If the air bags have been deployed, the material is no longer dangerous, and you will not have to take special precautions.

Airbag Systems Manufacturers:

- Autoliv, Inc. <https://www.autoliv.com/ProductsAndInnovations/PassiveSafetySystems/Pages/Airbags/default.aspx>
- Delphi Automotive Systems <http://delphi.com>
- Key Safety Systems, Inc. www.keysafetyinc.com
- TRW Automotive www.trw.com

Air bag & Pretensioner Recyclers:

- The Air Bag Center (Florida): www.airbagcenter.com (with related articles and How-to's)
- D& L Safety Air Bags (Michigan): www.safetyairbags.com

Reference Material:

- Insurance Institute for Highway Safety: www.iihs.org/iihs/topics/t/airbags
- US DOT (NHTSA) Safer Car: www.safercar.gov/Air+Bags
- Gas Laws Save Lives: The Chemistry Behind Airbags - Stoichiometry and the Gas Constant Experiment www.chemistry.wustl.edu/~edudev/LabTutorials/Airbags/airbags.html
- Authors: Rachel Casiday and Regina Frey, Department of Chemistry, Washington University, St. Louis, MO 63130

¹NOTE: Some pretensioners are mechanical and have no pyrotechnic mixture within them. Please check with the manufacturer for more information.

²NOTE: Air bag and pretensioner recycling must be through a reclamation facility or direct reuse, or another legitimate recycling operation. When in doubt, please contact the VT DEC.

Managing Automotive Antifreeze

What is antifreeze?

Antifreeze is a material that, in automotive applications, is used to protect engines against overheating, freezing in low temperatures, and corrosion. While antifreeze has many other uses and can contain either ethylene glycol or propylene glycol as a primary active ingredient, the antifreeze most commonly used in automobiles contains ethylene glycol and additives that inhibit corrosion.

Ethylene glycol is a toxic material with a sweet taste that is attractive to children and pets. Ingestion of enough ethylene glycol can cause respiratory failure, kidney failure, coma, and even death. Consequently, the proper management of spent ethylene glycol-based antifreeze is particularly important. Propylene glycol is generally not associated with adverse health effects and sometimes is even used as a food additive.

Automotive antifreeze, which is usually diluted with an equal amount of water, breaks down over time, forming acids that can corrode a vehicle's cooling system. During use, antifreeze can also become contaminated with trace amounts of fuel, metals and grit. Consequently, the replacement of spent antifreeze should be part of routine maintenance for all vehicles.

How is spent ethylene glycol-based antifreeze regulated?

Businesses: Due to the toxicity of ethylene glycol and the contaminants introduced through use, spent ethylene glycol-based antifreeze generated by Vermont businesses is regulated as hazardous waste under the Vermont Hazardous Waste Management Regulations (VHWMR). As a hazardous waste, spent ethylene glycol-based antifreeze can *either* be:

- **MANAGED AS HAZARDOUS WASTE** identified by the VT08 hazardous waste code that applies to “waste ethylene glycol and solutions containing greater than 700 parts per million of ethylene glycol;” *or*
- **RECYCLED** according to the ethylene glycol recycling exemption provided in section 7-204(i) of VHWMR.

Households: Although household-generated wastes are not subject to hazardous waste regulations, it is illegal to release spent antifreeze (or any other waste) onto the ground, or into waterways (e.g., storm drains, ditches, streams, lakes, etc.) or septic systems. In addition, all liquid wastes are banned from landfill disposal in Vermont. Household-generated antifreeze should be managed through the household hazardous waste collection program in your area. Contact your local solid waste management district for information.

What requirements must be met if spent ethylene glycol is managed as hazardous waste?

Although most businesses choose to recycle their antifreeze, the requirements that apply to businesses that manage spent ethylene glycol as hazardous waste depend on the types and total quantity of all hazardous waste that the business generates per month. For more information about hazardous waste management requirements, refer to the “Conditionally Exempt Generator Handbook” which is available on-line at: http://www.anr.state.vt.us/dec/wastediv/rcra/pubs/ceg_hndbk.pdf

What conditions must be met to satisfy the ethylene glycol recycling exemption?

In order to be exempt from regulation as hazardous waste, spent ethylene glycol antifreeze must be recycled for reuse either on- or off-site. In addition:

- Prior to recycling, the containers holding the spent antifreeze solutions on-site must:
 - Remain closed except when adding or removing spent material;
 - Be in good condition (i.e., no rusting, structural defects, etc.);
 - Be stored on an impervious surface, within a structure that sheds rain and snow; and
 - Be marked with words that identify the contents, like: “USED ANTIFREEZE TO BE RECYCLED.”

AND

- Any residue resulting from on-site recycling must be managed as hazardous waste.

Recycling methods include filtration, distillation, and ion exchange. Distillation and ion exchange restore antifreeze to the highest level of purity (for more information on antifreeze recycling technology contact the Environmental Assistance Office).

Is a hazardous waste manifest required to ship spent antifreeze for off-site recycling?

No. A manifest is not required when shipping an exempt waste. Nonetheless, some transporters may still require, for their own purposes, that a manifest be used when shipping antifreeze to an off-site recycling facility. In such cases, the business should use the VT99 waste code to identify the spent antifreeze as exempt (non-taxable) waste.

Is propylene glycol-based antifreeze regulated under the VHWMR?

No. Unless the business has reason to believe that the propylene glycol-based antifreeze has become sufficiently contaminated with metals or fuel as to exceed hazardous waste limits, it is not subject to regulation as hazardous waste.

BEST MANAGEMENT PRACTICES

- If the vehicle manufacturer’s warranty allows, substitute less toxic propylene glycol for ethylene glycol, or use recycled antifreeze.
- Test antifreeze for properties such as corrosion inhibition and freeze protection before replacing; only replace antifreeze when necessary.
- Investigate “extended life” antifreeze products. Manufacturers claim that these products last up to five years or 100,000 miles in automobile engines, and up to 300,000 miles in heavy-duty diesel engines (with the addition of an extender).
- Businesses managing spent antifreeze should contract with a commercial recycling service to recycle spent antifreeze on- or off-site.
- Businesses should manage all vehicle fluid wastes (e.g., antifreeze, oil, transmission fluid, gas) separately.

Managing Waste Fuel and Fuel/Water Mixtures

This Fact Sheet describes how businesses and municipalities can manage waste fuel and fuel/water mixtures under the Vermont Hazardous Waste Management Regulations (VHWMR). Although the focus is primarily on contaminated gasoline and gasoline/water mixtures, most of the information provided in this Fact Sheet applies to other liquid fuels (e.g., heating oil, diesel fuel, and kerosene).

How are waste fuels and fuel/water mixtures regulated under the VHWMR?

Under the VHWMR, waste fuel and fuel/water mixtures can be managed either as hazardous waste or, if certain conditions are met, as exempt material. Although waste fuel and fuel/water mixtures are subject to regulation as hazardous waste if they contain greater than 5% petroleum distillate material, or exhibit a hazardous waste characteristic (e.g., ignitability, toxicity), those materials may be managed according to the following two exemptions:

- VHWMR § 7-204(a)(1)(B) exempts wastes that are used or reused as an effective substitute for a commercial product without first being processed or reclaimed. An example is gasoline that is removed from a vehicle during maintenance and used as fuel in small engines.
- VHWMR § 7-204(a)(2)(B) exempts commercial chemical fuel products (exempt fuel products) when they are burned for energy recovery or used to produce a fuel.

Since the first exemption is self-explanatory, the remainder of this Fact Sheet focuses on managing waste fuel and fuel/water mixtures under § 7-204(a)(2)(B), a provision that is often referred to as the “fuel-to-fuel” exemption.

What conditions should be met in order for a waste fuel or fuel/water mixtures to be considered an exempt fuel product?

Vermont considers waste fuel and fuel/water mixtures to be exempt fuel products when the material has a recoverable quantity of fuel, and the generator:

- Manages the material as a commodity and in an environmentally sound manner prior to use as fuel (refer to the storage and handling requirements listed below).
- Does not mix the material with non-fuel hazardous waste.
- Ships the material within 45 days of generation to a legitimate facility for use as fuel or to produce fuel. A legitimate facility possesses the state and/or federal permits necessary to allow the facility to accept, treat, and/or burn for energy recovery *exempt fuel products* received from off-site.

MANAGING WASTE FUEL AND FUEL/WATER MIXTURES - FS10

- Maintains a written record of material shipped off-site (i.e., the type and amount of material shipped, the dates of generation and shipment, and the name, address and phone number of the receiving facility).

Any waste fuel or fuel/water mixture that is not managed as an exempt fuel product must be evaluated (by the waste generator) to determine if it is hazardous waste (e.g., contains greater than 5% petroleum distillate, and/or exhibits the hazardous waste characteristics of ignitability or toxicity). Wastes determined to be hazardous must be handled according to the requirements of the VHWMR.

Refer to the FACT SHEET - FS5 “Making a Hazardous Waste Determination” for more information about making hazardous waste determinations. Hazardous waste program Fact Sheets and other publications are available on-line by searching key words “Vermont Hazardous Waste Fact Sheets and publications.”

What are examples of fuel/water mixtures that can be managed as an exempt fuel product?

Examples include fuel storage tank bottom water; fuel/water mixtures collected from underground storage tank secondary containment systems, sumps, and spill buckets; and “bad gas” resulting from vehicle service work.

Tank cleaning wastes, rinsewaters, water that contains hazardous constituents not found in the fuel product, tank bottom sludge, and bilge water *are not considered exempt fuel products*.

How should waste fuel or fuel/water mixtures be stored and handled?

- Handled and stored in a manner that minimizes the possibility of fire, explosion or a release or discharge to air, soil, groundwater, or surface water;
- Stored in containers and tanks on an impervious surface, under cover;
- Label containers and tanks clearly (e.g., “Gasoline for Recycling”);
- Ensure that containers and tanks are in good condition;
- Keep containers and tanks closed and sealed except when adding or removing material;
- Keep freezable material in a heated space.

What are some additional best management practices?

- Keep spill and fire control equipment readily available;
- Inspect containers weekly for leaks;
- Store containers more than 50 feet from surface water and storm drains;
- If possible, secure storage areas against unauthorized entry.

How do I respond to a spill should one occur?

Refer to the FACT SHEET - FS4 “Hazardous Material Spill Response” for more information about spill response and spill reporting.

Mercury Containing Lamps & Auto Switches

What are the concerns about mercury?

Mercury is a highly toxic heavy metal that is released into the environment when mercury-containing lamps and switches are broken or thrown in the trash. Although lamps and switches contain a relatively small amount of mercury, the high volume of spent lamps (and to a lesser degree switches) generated in Vermont each year contributes to mercury contamination, particularly in fish and wildlife. State and federal fish advisories restrict consumption of certain freshwater and marine fish.

What kinds of lamps contain mercury?

Fluorescent lamps (linear and compact fluorescent) and high intensity discharge (HID) lamps contain mercury. HID is a term used to describe mercury vapor, metal halide, and high pressure sodium lamps.

How are mercury-containing lamps regulated?

Spent lamps, whether generated by businesses or households, cannot by law be disposed in the trash, and if possible, should be recycled. Spent lamps generated by businesses and institutions are subject to Universal Waste Management Standards contained in the Vermont Hazardous Waste Management Regulations (Subchapter 9). See the FACT SHEET - FS21 “Universal Waste” for more information.

What are the options for recycling mercury-containing lamps?

The following recycling options are available to homeowners and businesses:

- Contact your local solid waste district or municipality for information about the availability of nearby collection sites or household hazardous waste collection events. Some hardware stores or other retailers may offer collection programs.
- Some electrical wholesale suppliers accept lamps from their customers for recycling.
- Businesses that already use a permitted hazardous waste transporter to pick up hazardous wastes may be able to ship spent lamps using that same transporter.
- Lamp recycling facilities (out-of-state) have pick-up and mail-back programs for spent lamps.

Are there special storage requirements for businesses?

Yes. Under the Universal Waste Management Standards, businesses are required to package lamps in structurally sound containers (boxes) that prevent breakage. Boxes or containers must be:

- Kept closed and sealed with tape once full (Do not tape lamps together);
- Labeled with words like “Universal Waste Lamps” or “Waste Lamps;”
- Stacked no higher than five feet; and
- Transported to an approved collection center within one year unless additional time is necessary to accumulate enough lamps for shipment. Businesses may self-transport lamps without a manifest.

Can the so-called “green tip” or low mercury lamps be disposed in the trash?

No. Even though some manufacturers now make lamps that are low in mercury, these lamps are also prohibited from disposal as solid waste in Vermont.

Is crushing an acceptable method of managing spent lamps?

No. Vermont regulations prohibit the intentional breaking or crushing of mercury-containing lamps since studies have shown that even enclosed crushing devices designed specifically for lamps release a significant amount of mercury vapor. Although lamp crushing devices are commercially available for the purpose of increasing lamp storage space (decreasing lamp volume), the use of such devices is prohibited without full certification under the VHWMR. Lamps that are intentionally broken must be managed as hazardous waste.

What if a lamp accidentally breaks?

As is the case when managing any fragile waste, lamps will occasionally break when handling and/or storing them. The waste material generated through this “*incidental breakage*” of lamps can be managed as universal waste provided it is cleaned up immediately and placed in a sealed container. In addition, any lamps that show evidence of breakage must also be placed in a sealed container for continued management as universal waste. Containers that are used to store broken or damaged lamps must be kept closed (except when adding waste), structurally sound, compatible with the lamps (i.e., a metal or plastic container), and must lack evidence of leakage, spillage or damage. Containers used to store broken or damaged lamps must also be labeled to identify their contents as universal waste lamps and to indicate that the lamps are broken. Broken or damaged lamps may be shipped to a destination facility along with containers of intact universal waste lamps.

If a lamp is broken after being placed in a shipping container (e.g., box, drum, etc.), the lamp should be left in the shipping container, and the container should be sealed immediately.

These are additional clean-up suggestions.

- Keep all people and pets away from the breakage area to prevent mercury powder from being tracked into other areas.
- Keep the area well ventilated.
- Assemble the necessary supplies (latex gloves, tweezers, adhesive tape, and a puncture-resistant container) before cleaning up.
- Using the latex gloves, carefully pick up any broken glass and place it in container. It may be necessary to use the tweezers and adhesive tape to pick up any small pieces of glass and powdery residue remaining on the spill surface. DO NOT VACUUM.

MERCURY CONTAINING LAMPS & AUTO SWITCHES - FS11

- After clean-up is complete, place any other material that came in contact with the mercury powder into the container.
- Contact your municipality, Solid Waste District, or this office for disposal options.

Mercury-Containing Auto Switches

Many vehicles (model year 2002 and older) contain mercury tilt switches in trunk and hood convenience light assemblies. The mercury tilt switch is a small metallic pellet in the light assembly and it contains liquid mercury.

If you replace or discard an old trunk or hood convenience light assembly, you can tell if mercury is present in the tilt switch (pellet) by shaking it. You will hear the liquid in the pellet. If it does not contain mercury, you will hear the metallic ball bearing inside. Mercury-containing switches are a universal waste. See the FACT SHEET - FS21 "Universal Waste" for more information.

Some anti-lock brake G-Force sensors contain several embedded mercury switches. ABS sensors were used in Jeeps of all types, Ford Explorers and Broncos, and 1990-1996 Subaru (Legacy and Impreza AWD with 5MT). These mercury-containing sensors are less common than convenience lights with mercury. Any old or replaced sensors in these vehicles should be handled as Universal Waste.

Motor Vehicle Air Conditioning

What is CFC-12 and why does it pose an environmental and human health concern?

CFC-12 (also known by the trade name Freon) is a refrigerant used in automobile air conditioners. Scientists worldwide believe that certain man-made chemicals such as CFC-12 are destroying the ozone layer 10-30 miles above the earth's surface. The ozone layer acts as a blanket in the atmosphere, protecting us from the sun's harmful ultraviolet (UV) radiation. Overexposure to UV radiation has been determined to cause skin cancer, cataracts and suppression of the human immune system.

How is CFC-12 regulated?

The 1990 Clean Air Act Amendments banned the production of most ozone-depleting substances, including CFC-12, by the end of 1995. However, the use of CFC-12 is still permitted as long as supplies are available. There is no requirement for car owners to convert their vehicle's air conditioning system to an alternative refrigerant.

State and federal regulations do not prescribe any particular service as long as technicians are certified to work with refrigerant and any recycling equipment he or she uses meets EPA standards.

What is HFC-134a?

HFC-134a has been selected by engineers for automotive manufacturers as the replacement refrigerant for CFC-12. Although HFC134-a is not an ozone-depleting chemical, it is a "greenhouse gas" (i.e., a contributor to global warming) and therefore cannot be vented to the air.

Are there other substitutes that are considered safe to use?

EPA evaluates all substitutes for CFC-12 under its Significant New Alternatives Policy in order to determine if they pose any risk to human health or the environment. Currently, HFC-134a is the only alternative which has been fully tested and specified by automakers in their guidelines.

How do technicians become certified?

Technicians who repair or service air conditioners must be certified by an EPA-approved organization. To be certified, technicians must pass a test demonstrating their knowledge in the importance of refrigerant containment, the use of equipment and the effects of ozone depletion. You can find a listing

of approved certification programs by going to the following web site: <https://www.epa.gov/section608/section-608-technician-certification> or by calling the Environmental Assistance Office Hotline.

How is equipment certified?

Service shops must also certify to EPA that they have acquired and are properly using approved refrigerant recovery equipment. The certification statement must include the name and address of the business, the name of the equipment manufacturer, equipment model and serial number, and equipment date of manufacture.

A sample certification form may be found at: <https://www.epa.gov/section608>. A list of approved equipment for CFC-12 recovery and/or recycling can also be found at this web site. Recover/recycle equipment cleans the refrigerant so that oil, air and moisture contaminants reach acceptably low levels. Certain equipment models can recycle either CFC-12 or HFC-134a refrigerants.

What can be done with recovered CFC-12?

Recovered CFC-12 is almost always recycled by either: returning it to the vehicle for reuse or storing it in a holding tank until such time as it is sent to an off-site reclamation facility. Recovered CFC-12 that is not reused directly or reclaimed for further use must be managed as a hazardous waste under Vermont's Hazardous Waste Management Regulations.

WHAT ARE SOME BEST MANAGEMENT PRACTICES?

- Evacuate and recover refrigerant before servicing to avoid releases.
- Inspect hoses, connections and condenser for leaks. Consider purchase of an electronic leak detector. Avoid using leak detecting products containing CFC-12.
- Don't mix CFC-12 and HFC-134a since contaminated refrigerant must be sent off-site for reclamation.
- Purchase refrigerant in 15lb. containers or greater.
- Retrofit air conditioner to use HFC-134a instead of CFC-12. Lubricants, seals, fittings, etc. used with CFC-12 are generally not compatible with systems retrofitted for HFC-134a. When in doubt as to proper retrofitting procedures, always consult with the air conditioner manufacturer. Motor vehicles, model year 1995 or newer, use HFC-134.

Oil Filters

How are spent oil filters regulated?

Used oil filters that are generated by businesses are regulated as hazardous waste unless they are managed according to the exemption for metal encased oil filters provided in section 7-203(o) of the Vermont Hazardous Waste Management Regulations (VHWMR). All household-generated wastes, including spent oil filters, are exempt from regulation as hazardous waste under VHWMR section 7-203(a).

What conditions must be met in order for oil filters to be exempt?

While the following conditions must be met in order for business-generated oil filters to be exempt from regulation as hazardous waste, businesses should also consider implementing the “best management practices” listed on the following page. The exemption requires that:

- The filters are not terne plated. Terne is a lead/tin alloy that typically is used on filters for heavy duty vehicles. Terne plated filters can be hazardous due to their lead content.
- The filters are drained using one of the following methods:
 - Puncturing the filter anti-drain back valve or the filter dome end and hot draining*;
 - Hot draining and dismantling;
 - Any other equivalent hot draining method that will remove used oil; or
 - Draining and crushing using a mechanical, pneumatic, or hydraulic device designed for crushing oil filters.
- The filters are not mixed with any hazardous waste (e.g., gasoline or oily absorbents).
- All drained oils are collected and managed in accordance with the VHWMR.

Where can I send exempt oil filters?

Although exempt oil filters, which in most cases are made of steel, can be disposed of as solid waste, **THE DEC STRONGLY ENCOURAGES BUSINESSES AND HOUSEHOLDS ALIKE TO RECYCLE THEM AS SCRAP METAL.** Check with local scrap yards or contact your solid waste district, planning commission, or municipality for information about recycling opportunities.

BEST MANAGEMENT PRACTICES FOR SPENT OIL FILTERS:

- Hot drain filters for at least 12 hours. Filters that immediately drip oil when picked up are not considered drained.
- Puncture the dome (top) of the filter, and drain it with the filter threads facing up. This method bypasses the check valves in the filter, ensuring that most of the oil is removed.
- Manage the oil drained from filters with other used oil.
- Store drained or crushed filters in a closed, leak proof container on an impervious surface.
- Recycle properly drained or crushed filters with scrap metals.
- Businesses that routinely generate large numbers of oil filters should consider purchasing an oil filter crusher. These devices compress oil filters into “pucks” allowing generators to fit more spent filters into shipping containers, while reducing recycling or disposal costs. If spent filters are being sent for recycling, contact the recycler prior to crushing since some recyclers do not accept crushed filters (e.g., recyclers that separate the metal from filtration media).
- If you crush filters, use a crushing area with an impervious surface.

**Hot draining means draining oil filters at temperatures near the operating temperature of an engine.*

Oily Wastes

What are Oily Wastes?

Oily wastes represent a broad category of waste materials contaminated with petroleum-based oils. The Vermont Hazardous Waste Management Regulations (VHWMR) stipulate that wastes generated by businesses or municipalities that are greater than 5% by weight petroleum distillates are hazardous wastes identified by the VT02 hazardous waste code. Although some petroleum-containing wastes are regulated under additional hazardous waste codes because they are ignitable or contain contaminants like benzene (i.e., anything contaminated with gasoline), this Fact Sheet only covers wastes contaminated with oil.

Examples of oily wastes may include used:

- Absorbents like pads and booms;
- Kitty litter and other clay-based absorbent materials;
- Organic, granular absorbents like saw dust, corn cob or peat-based products;
- Floor sweepings;
- Sludge or grit from floor drain troughs;
- Oil-soaked dirt.

Are all oily wastes regulated as hazardous waste?

No. Again, only wastes that contain more than 5% by weight petroleum distillates are regulated under the VT02 waste code. The VHWMR do contain exemptions for some oily wastes so long as certain conditions are met. These “conditional” exemptions are identified later in this Fact Sheet.

What is the best way to determine if wastes are more than 5% by weight petroleum distillates?

For absorbents, the weight of the uncontaminated material can be compared with its weight after use to see if there has been at least a 5% increase. If the contaminated material is heavier by more than 5%, it is probably hazardous waste (dirt, water and other non-petroleum contaminants can also account for some of the increase). Manufacturers of most oil-absorbing products claim that they will absorb 50% or more of their original weight in oil.

For oil-contaminated liquids, dirt or other debris, a sample can be taken to an environmental laboratory and analyzed for total petroleum hydrocarbons (TPH). Copies of the test results should be kept on

file. Analytical testing does not have to be performed again unless the generator (the business or municipality) has reason to suspect that the composition of the waste has changed.

What if contaminated material is less than 5% by weight petroleum distillates?

Oily waste less than or equal to 5% petroleum distillate can be disposed of as regular solid waste in the trash. Contaminated dirt or floor sweepings should never be spread outside to mix with uncontaminated soils.

Wastewater that has picked up small amounts of oil must pass through an oil/water separator (see FACT SHEET - FS15 “Oil/Water Separators”) prior to discharge to a municipal wastewater treatment plant. Oily wastewater should never be discharged to an on-site septic system.

What are oily wastes that are conditionally exempt from the VHWMR?

The following oily wastes greater than 5% by weight petroleum are exempt from regulation as hazardous wastes (and therefore are not considered in determining the generator status of the business) so long as they are managed with conditions stipulated in the VHWMR.

- Oil filters (section 7-203(o)); (See FACT SHEET - FS13 “Oil Filters.”)
- Commercially-Laundered Wipers (section 7-203(w)); (See FACT SHEET - FS19 “Shop Rags Contaminated with Used Oil or Hazardous Waste.”)
- Petroleum-contaminated soil (section 7-203(p)); this exemption is intended for contaminated properties and has many stringent conditions with it.
- All household wastes (section 7-203(a));
- Reusable absorbents (section 7-203(x)); see next question.

Can oil-soaked absorbent material be wrung out and reused?

Yes. The VHWMR provide for the reuse of wring-able pads, booms and other absorbent materials so long as they are processed and reused on site. If contaminated absorbents are stored prior to processing, containers must be:

- Marked with words that identify the contents (i.e., “oily absorbents for reuse”);
- Kept closed except to add or remove material;
- In good condition; and
- Located on an impervious surface and if kept outside, within a structure that sheds rain and snow.

What about any oil that is recovered?

Free liquid oil that is recovered by the wringing of absorbent material, skimmed from an oil/water separator, or otherwise drained, separated or removed from materials contaminated with oil, may be managed as “used oil” under Subchapter 8 of the VHWMR. See FACT SHEET - FS22 “Used Oil” and FACT SHEET - FS3 “Burning Used Oil Fuel.”

Can oily wastewater be evaporated?

After free oil has been removed, oily wastewater may be evaporated provided:

- It is non-hazardous OR hazardous waste only because it contains greater than 5% by weight petroleum distillate;
- The facility has received approval from Vermont’s Air Pollution Control Division to operate evaporation equipment; and
- Oily residue remaining after evaporation is managed either as “used oil” or as hazardous waste.

BEST MANAGEMENT PRACTICES

Identify the circumstances that result in oil reaching the shop floor. Implement a preventive maintenance program to minimize the generation of oily waste. Common techniques include:

- Using drip pans, funnels, drain trays, etc. to catch and transfer fluids to appropriate containers;
- Cleaning floors regularly to remove dirt before it has a chance to become contaminated;
- Avoiding the sweeping of dirt and debris into floor troughs or basins.
- If a spill does occur, avoid the use of absorbents if possible by collecting liquid oil with a squeegee or oil-only wet-vacuum. Oil can then be managed as “used oil.”
- Keep a small supply of absorbent material on-site to clean up residual oil that cannot be collected.
- If it is necessary to use absorbent materials to clean up an oil spill, use reusable pads or booms if possible. Otherwise use absorbent material(s) that has a high absorbency to weight ratio, and use it until saturated.

Oil/Water Separators

What is an oil/water separator?

Oil/water separators are underground vaults, usually constructed of concrete, installed between a drain or drain network and the connecting sewer pipe. These vaults are designed with baffles to trap sediment(s) and retain floating oils and grease, while allowing water to discharge. The large capacity of these separator systems slows discharge water allowing oil to float to the surface and solid material to settle to the bottom.

Who typically needs an oil/water separator?

Any business or facility that frequently discharges oily or sediment-laden wastewater to a sewer system should install a separator system. Many local sewer ordinances require an oil/water separator for certain activities such as commercial car washes, vehicle service facilities with floor drains or facilities with a vehicle washing bay. Check with your local town office or contact your wastewater treatment plant operator to see if your town has such a requirement.

What is required before an oil/water separator is installed?

You should check with your local town office to better understand any local sewer ordinances or requirements that may apply. Before a separator system is installed in an existing facility you need to contact the Department of Environmental Conservation's regional office serving the area in which your facility is located. In some cases an existing facility may need a permit, and in some cases it may not. A separator being installed in a new facility will require a wastewater permit prior to installation. See the regional office map for the VT DEC to which office serves your town. Plumbing supply contractors or wastewater engineers can be helpful in choosing a separator that is appropriately sized for your facility. Contact your local permit specialist if you have questions about permit requirements for any wastewater activity.

How do I know when it needs to be maintained or cleaned?

Just because an oil/water separator is still draining, it may not be functioning at its full efficiency. Like any filtration system, an oil/water separator needs to be maintained and cleaned on a regular basis. The efficiency of a separator system is most affected by settled solids or sludge on the bottom of the separator, and by oils floating on the water surface. The VT DEC recommends that an oil/water separator be inspected every six months to a year and the system be cleaned when needed. A separator with less sediments and lower amounts of oil entering the system may only need to be cleaned every few years.

Who can I call to pump out and clean my separator system?

Oil/water separators can be cleaned by a professional contractor specializing in environmental clean up work. You can contact the Environmental Assistance Office for a list of contractors who do this type of work. These companies have special vacuum trucks that can easily pump materials ranging from liquid, to sludge and dirt slurry. If the liquid is less than 5% by weight petroleum distillates it can be sent to a wastewater treatment facility with approval from the operator. If the solids are less than 5% by weight petroleum distillates they must be land filled. If either the liquid and/or solids contain **GREATER THAN 5%** by weight petroleum distillates they must be properly disposed of as a hazardous waste. Please contact the EAO if you have questions about trying to clean and service your own separator system.

What should not go down the drain and into an oil/water separator?

Antifreeze, degreasers and detergents can emulsify (break up) oil into small droplets so the oil does not float to the surface. Fuels, alcohols or other solvents can also emulsify oil, as well as cause accumulated vapors, posing a threat to facility employees and/or wastewater treatment plant workers. Concentrated amounts of oily products will decrease the effectiveness of the separator system and require more frequent potentially expensive cleanings. Oil/water separators are not designed to treat heavy metal-bearing wastewater. These types of discharges are typically hazardous waste and must be handled and disposed of accordingly.

What can you do to maintain and help keep your oil/water separator clean?

You can save maintenance and service costs by minimizing the amount of oil and sediments that enter your system. By frequently sweeping sand and sediments from the floor, you will greatly reduce the potential of those materials building up in your separator. By using drip pans and oil soaking absorbent materials you will greatly reduce the amount of oils and grease that enter your separator.

Another way to remove oil is to use absorbent pads and socks on the floor and within your floor drain system. These pads and socks float on water and attract and retain oil allowing the water to pass by. Place them in the inlet chamber or within the floor drain network to trap oils before they have a chance to migrate into the separator system. Check the pads and socks often so they don't get fully saturated and become less effective. Some pads can be wrung out and reused if handled properly. Remember to properly handle and dispose of any oils that are extracted from such activities, or manage them as used oil if they are not contaminated. After use any such material must be disposed of as oil soaked hazardous waste. See Fact Sheets for more information.

Petroleum-Based Parts Cleaning

This Fact Sheet covers parts washers that use petroleum-based solvents such as mineral spirits and naphtha to clean oil and grease from metal and other non-porous parts. Petroleum-based solvents, like other petroleum products (e.g., gasoline, fuel oil), are derived from crude oil and have environmental, health and safety concerns associated with them. Solvent cleaning performed in vapor degreasing units is not addressed here, nor is aqueous parts cleaning, which is the subject of a separate Fact Sheet.

How is petroleum-based parts cleaning regulated?

Petroleum-based parts cleaning solvents are subject to regulation under both the Vermont Hazardous Waste Management Regulations (VHWMR), which affect the proper management and disposition of spent solvent, and section 5-253.14 of Vermont's Air Pollution Control Regulations, which establishes operating standards for minimizing the release of volatile organic compounds (VOCs) during use.

Why is spent petroleum-based solvent a hazardous waste?

Under the VHWMR, spent petroleum-based solvents are regulated as hazardous waste because they contain greater than 5% by weight of petroleum distillate, and are identified by the VT02 hazardous waste code. These solvents can further qualify as hazardous waste if they have either a flash point less than 140° F and thus exhibit the characteristic of ignitability (identified by the D001 waste code), or if they become contaminated with certain toxic constituents during use.

In most cases, if the solvent is not ignitable at the time of purchase, it is unlikely that it will become ignitable through use. Conversely, parts cleaning solvent can easily become contaminated through use with toxic metals like chromium or lead (from parts) or even very small amounts of other solvents such as trichloroethylene or methyl ethyl ketone. Since these contaminants can cause spent petroleum-based solvent to be more strictly regulated, it is important to use parts washers carefully. In particular, avoid using cleaning (and other spray) products that contain regulated solvents over parts washing sinks or in a way that allows them to mix with the parts washing solvent.

In all cases, it is up to the generator to make a "determination" whether spent parts cleaning solvent is a hazardous waste based on testing, generator knowledge or a combination of the two. For more information about making a hazardous waste determination (and other requirements), refer to the "Conditionally Exempt Generator Handbook" available by calling 802-241-3888 or 800-974-9559, or searching online using key words 'Vermont Conditionally Exempt Generator Handbook'.

What if a parts washer is serviced by an outside contractor?

Many businesses choose to lease parts washers from an outside contractor who periodically replaces spent solvent with fresh solvent. The extent to which the VHWMR apply to the spent solvent depends on how the contractor manages the spent solvent after pick-up. Solvent that is used directly as an ingredient in an industrial process to make a product (i.e., without first processing or reclaiming the solvent) is exempt from regulation as a hazardous waste under section 7-204(a) of the VHWMR. In this case, the solvent does not count towards the total quantity of hazardous waste generated on-site.

Alternatively, in cases where the contractor either sends the spent solvent for fuel-blending, or must first reclaim the solvent before reusing it, the spent solvent is regulated as hazardous waste and the business using the parts washer is considered the generator of that waste. As with any hazardous waste, the weight of spent solvent must be counted toward the total quantity of hazardous waste generated by the business for the purpose of determining generator status. Also, it is important to note that even if the contractor completes the required documentation for shipping and tracking the waste, the business using the parts washer is still considered the generator.

What if my parts washer is equipped with a filter to extend solvent life?

Although the use of filters to extend solvent life in a parts washer is considered a best management practice, spent filters and sediment are likely to be hazardous waste for the same reasons as spent solvent. As such, unless a generator determines otherwise, spent filters (and sediments) are assumed to be hazardous waste and must be stored in properly labeled containers that are kept covered to prevent solvent from evaporating. Even in situations where spent solvent is being reused directly, (and is therefore exempt under section 7-204(a) as explained above), spent filters are assumed to be hazardous waste.

Can spent petroleum-based solvent be mixed with used oil and burned in approved equipment?

Spent petroleum-based solvent that is hazardous waste only because it is ignitable (and because it contains petroleum distillates) may be mixed with used oil provided the resulting mixture is not ignitable. Such mixtures may be burned in approved space heating equipment provided all standards applicable to on-site used oil fuel burning are satisfied. See the FACT SHEET - FS3 “Burning Used Oil Fuel” for more information. It is important to realize, however, that even though spent petroleum-based parts cleaning solvent can be mixed with used oil, spent solvent by itself does not meet the definition of “used oil” and therefore cannot be managed under the Used Oil Management Standards of Subchapter 8 of the VHWMR.

What are terpene solvents?

Terpenes are organic solvents derived from natural sources such as pine trees and citrus fruit that generally have strong characteristic odors. Although terpenes are considered less toxic to use than petroleum-based solvents, they are comprised of volatile organic compounds and consequently can exhibit the hazardous waste characteristic of ignitability. Spent terpene solvents may also be subject to further regulation as a result of contaminants introduced during use.

What requirements govern parts washers during use?

Vermont's Air Pollution Control Regulations require that the following standards be met to minimize emissions of volatile organic compounds from parts cleaning operations:

- Parts cleaning units must have a cover and the cover must be kept closed except when parts are being cleaned.
- If the parts washer is designed to spray solvent, the pressure of the spray cannot exceed 10 psi.
- Only parts that are non-porous and non-absorbent can be washed.
- Any leaks from a parts washer must be repaired.
- Cleaned parts must be drained until dripping stops.

BEST MANAGEMENT PRACTICES

- Wipe off parts with a rag or wire brush before washing with solvent.
- Drip racks or trays that route solvent back into the parts washer can help increase drainage from parts (and minimize solvent loss).
- Carefully review Safety Data Sheets to avoid using hazardous materials as much as possible – spent solvent with a flash point greater than 140° F is not an ignitable hazardous waste.
- Keep accurate records of solvent purchases and the disposal of spent solvent and filters.
- Never use aerosol spray cleaners over a parts washer as those cleaners can introduce new solvents that can cause the parts washing solvent to be more strictly regulated.
- Use filters to extend solvent life.
- Consider a safer alternative like a terpene or water-based (aqueous) cleaner. See FACT SHEET - FS1 “Aqueous Parts Cleaning.”

Scrap Metal, Recycling, and Landfill Disposal Bans

What Is Scrap Metal?

Scrap metal means bits and pieces of metal parts (rods, bolts, wheel weights) or metal pieces that may be combined together with bolts or solder (radiators, scrap vehicles) which can be recycled. Some scrap parts contain lead, a toxic substance and potential pollutant. Scrap catalytic converters contain platinum, a valuable, recyclable metal. Managing scrap metal safely will help prevent pollution at your salvage yard.

Lead Scrap

Lead wheel (tire) weights and battery cable ends are common sources of lead. Lead is also found in radiators, heater cores, steering columns, soldered parts (circuit boards) and electronic components. Before removing parts such as radiators or heater cores, drain fluids carefully to prevent spills and manage them appropriately. If you need to use a cutting torch, wear respiratory protection, such as a respirator with appropriate filters, to reduce the risk of breathing airborne lead that may be released by heating lead scrap.

HEALTH ALERT

To avoid generating toxic lead fumes, use a reciprocating saw rather than a cutting torch to remove lead portions from scrap parts when appropriate. Store scrap items containing lead in a covered container capable of handling the excessive weight of the lead.

- Marking the container “Lead Scrap” will help ensure non-lead scrap is not mixed with it.
- Large scrap items, such as radiators that cannot be stored in a covered container, should be stored to prevent contact with rain, snow and storm water.
- Battery cable ends can be left attached to the battery and recycled along with the battery.
- Recycle lead parts with a metals battery recycler.

HEALTH ALERT

After working with lead scrap, always wash well before smoking or eating to avoid ingesting lead.

Catalytic Converters

Store waste catalytic converters in a marked container to prevent mixing with other scrap. Recycle catalytic converters with a catalytic converter collection center.

Cores

Core parts, such as alternators, master brake cylinders, starters and brake pads should be returned to a parts supplier for rebuilding. Before returning brake cylinders or any other part containing fluid, be sure to drain and manage the brake fluid appropriately.

Other Recyclable Materials

Common recyclable materials in the Vehicle Service sector that must be recycled under Vermont's new Universal Recycling Law (Act 148) are: (1) cardboard, including corrugated and boxboard; (2) glass containers; (3) compostable yard and food waste; (4) newsprint; (5) office paper; (6) steel and aluminum cans; and (7) plastic containers (made of HDPE or PET). For complete information, search on-line using key words 'Vermont Universal Recycling'.

Landfill Disposal Bans

See FACT SHEET - FS6 "Materials Banned From Vermont Landfills."

Scrap Tires

In recent years, recycling markets for scrap tires have been strong because numerous uses for scrap tires have been developed. Today, recycling scrap tires makes more sense than disposal. Disposal of scrap tires represents wasted resources, energy and money.

Why are Scrap Tires of concern?

Waste tires are bulky waste which can not be managed along with normal solid waste because of the problems they create when landfilled. When buried in a landfill, tires tend to “float” to the surface over time and disrupt landfill covers as well as landfill gas and leachate collection systems.

Piles of scrap tires present a number of environmental, health and safety hazards. When tire piles catch fire, the melted rubber generates oil and other toxic run-off that can pollute surface and groundwater. The air trapped in tire piles makes fires difficult to extinguish, often causing them to burn uncontrollably. Furthermore, rainwater accumulated in waste tires creates a perfect breeding ground for disease transmitting mosquitoes.

How should scrap tires be managed?

Scrap tires are banned from landfill disposal by Vermont statute. Furthermore, scrap tires may not be burned as fuel without a permit issued by the Vermont Air Pollution Control Division.

VEHICLE SERVICE SHOPS THAT GENERATE SCRAP TIRES MUST HIRE A LICENSED TIRE HAULER TO REMOVE THEIR TIRES.

Please contact the Solid Waste Management Program at 802-828-1138 for a list of licensed tire haulers. This list is also available on-line by searching key words ‘Vermont permitted haulers’. Vehicle service shops should also make sure they know where their scrap tires are going and how the tires are eventually processed. Vermont companies in the business of storing or processing scrap tires must have a permit from the Solid Waste Management Program.

Some of the ways scrap tires are being used include:

- Burning as a tire-derived fuel in cement kilns or electric power plants;
- Retreaded – retreading usually works best for truck tires;
- Shipped to firms that process them to produce crumb rubber or chips;
- Used as a construction material (i.e., intact for retaining walls or shredded for use as a lightweight fill). Approval may be required by the Solid Waste Management Program for some

uses. See the Acceptable Use Procedure on-line by searching key words 'Vermont Procedure Addressing Acceptable Uses of Solid Waste', and contact the Solid Waste Management Program at 802-828-1138.

What are some best management practices?

- Do not let tires piles become too large. Ship them as soon as a full load has been accumulated.
- Keep tire piles orderly and accessible from all sides.
- Either cover or store scrap tires in an enclosure until shipped to prevent water from accumulating in the casings. This will help prevent mosquitoes from breeding in the scrap tires.
- Re-market tires with more than 30% serviceable tread.
- Separate the highest quality casings for retreading.
- Encourage customers to regularly check tire pressure and rotate tires according to manufacturers' recommendations, as well as maintain proper wheel alignment and tire balance to prolong tread life.

Shop Rags Contaminated with Used Oil or Hazardous Waste

This Fact Sheet covers management options for Vermont businesses that handle shop rags contaminated with used oil or hazardous wastes such as spent solvent and ink. Shop rags (also called wipes, wipers, or towels) generally fall into two categories: rags that are intended for reuse and made of woven cotton or a polyester blend, and disposable (non-woven) rags made of wood pulp or a polyester blend. This Fact Sheet describes the conditions that must be met in order for reusable shop rags to be considered exempt from regulation under the Vermont Hazardous Waste Management Regulations (VHWMR), and when contaminated rags that are to be disposed of are subject to full regulation as hazardous waste.

When are contaminated shop rags considered exempt from regulation as hazardous waste?

Contaminated shop rags are considered exempt from regulation as hazardous waste provided:

1. The rags are picked up and cleaned under a contractual agreement with a commercial laundry service.
2. Hazardous waste is not intentionally added to (i.e., poured onto) the rags beyond what is picked up through normal use of the rag, and no free liquid is present in the rags (i.e., no liquid can be wrung from the rags).
3. Prior to being picked up by a laundry service, the rags are accumulated and stored on-site in containers that are:
 - Marked with words that identify the contents, such as “Used Rags for Laundering;”
 - Kept closed except to add or remove contaminated rags (if laundry bags are used, they must be kept inside a closed container);
 - In good condition (i.e., no apparent structural defects); and
 - Stored on an impervious surface, and if stored out-of-doors, within a structure that sheds rain and snow.
4. The laundering facility manages:
 - Wastes from laundering contaminated rags in accordance with local, state and federal regulations; and
 - Wastewater in accordance with local, state and federal wastewater discharge requirements.

It is a good idea to ask the laundry service to provide written verification that they hold all applicable permits and are in good standing with the municipal wastewater treatment facility in the town in which they operate.

Since shop rags that are managed according to the conditions described above are considered to be exempt from regulation as hazardous waste, they do not have to be counted toward your facility's monthly hazardous waste generation rate, or shipped using a manifest. You should be aware, however, that the U.S. Environmental Protection Agency is in the process of developing a rule for shop rags that, if adopted, could supersede this policy.

Can I self-laundry contaminated shop rags at my own facility?

No. In order to be considered exempt from regulation as hazardous waste, contaminated rags must be picked up and laundered by a commercial laundry service. By self-laundering contaminated shop rags, you could inadvertently contaminate groundwater.

Can I allow hazardous waste to evaporate from contaminated shop rags?

No. The evaporation of hazardous waste is specifically prohibited under Section 7-302(a) of the VHWMR. Once shop rags are no longer usable, they must be placed in a marked container and managed according to the requirements described in this Fact Sheet.

How do I manage shop rags that I intend to dispose of?

Any shop rags that are destined for disposal and that are:

- Contaminated with a "listed" hazardous waste (for example, rags that contain greater than 5% by weight of petroleum distillates, or any amount of an "F-listed" solvent); and/or
- Exhibit a hazardous "characteristic"

must be managed as hazardous waste according to the requirements of the VHWMR. For more information about listed hazardous wastes, the hazardous waste characteristics, and basic hazardous waste management requirements, please refer to the Conditionally Exempt Generator Handbook, which is available on-line by searching key words 'Vermont Conditionally Exempt Generator Handbook'.

Shop rags that are not contaminated with hazardous waste and do not exhibit a hazardous waste characteristic may be disposed of in the regular trash.

What else should I know about managing shop rags?

Reusable shop rags contaminated with an ignitable material must be stored in a closed metal container according to Vermont Occupational Safety & Health Act (VOSHA) requirements. For information regarding VOSHA requirements, you may contact the Vermont Department of Labor at 802-828-2765 or VOSHA's non-regulatory assistance program, Project WorkSafe, at 888-723-3937.



WHAT ARE SOME BEST MANAGEMENT PRACTICES?

- Store containers holding contaminated shop rags away from ignition sources.
- Avoid saturating rags such that they can not be laundered.
- Use drip pans, funnels, drain trays, etc. to prevent oil and other fluids from reaching the shop floor, thus eliminating the need for clean-up.
- Improve housekeeping and preventative maintenance practices to minimize need for clean-up. Identify circumstances that routinely require the clean-up of fluids, and develop a spill prevention plan that identifies measures to address each of circumstances. Involve facility workers in the planning process – they know how and why spills happen.
- Remove excess solvent or oil from rags before laundering by wringing them with a mechanical device, and then recycle the collected fluids.
- When a spill is more than just a drip, clean the fluids up with a wet-vac or squeegee and dust pan, and then recycle the collected fluids.

Federal Spill Prevention, Control, and Countermeasure Regulation

The U.S. Environmental Protection Agency's oil pollution prevention regulation (Federal Spill Prevention, Control, and Countermeasure (SPCC) Regulation - 40 CFR 112) requires facilities that are subject to regulation to prepare and implement a plan to prevent any discharge of oil into navigable waters or adjoining shorelines of the U.S. The plan is referred to as a Spill Prevention, Control, and Countermeasure (SPCC) plan.

What is an "Oil"?

"Oil" is any kind or in any form, including, but not limited to: petroleum, fuel, sludge refuse, oil mixed with wastes other than dredged spoil; fats, oils or greases of animal, fish, or marine mammal origin; vegetable oils, including oil from seeds, nuts, fruits, or kernels; and other oils and greases, including synthetic oils and mineral oils.

Who is regulated?

Facilities which meet the following criteria are regulated by the SPCC regulation:

1. Non-transportation-related fixed facilities, including support equipment;
2. Facilities with a total aboveground storage capacity greater than 1,320 gallons (count all drums or vessels greater or equal to 55 gallons) or a total underground storage capacity greater than 42,000 gallons, and;
3. A reasonable expectation that a discharge to navigable waters or adjoining shorelines of the U.S. could occur. (EPA Region I interprets this as any VT facility - unless a case is made against it.)

NOTE

- **1,320 gallons is equivalent to 24 full 55-gallon drums of oil.**
- **UST certified tanks (that are subject to 40 CFR 280 and 281) are exempt from SPCC.**
- **You must count the potential storage capacity of all on-site oil vessels, whether they contain virgin product or used/waste oil.**

What is required?

If your facility meets the three items listed above, you must comply with the SPCC regulation. The SPCC Plan is to be kept on-site and available for regulatory inspections, and must include, but is not limited to:

- Spill predictions
- Facility drainage
- Oil spill history
- Professional Engineer certification
- Facility inspections
- 5-year plan review
- Loading/unloading trucks
- Secondary containment or diversionary structures (outdoors)
- Site security
- Management approval
- Training and spill briefings

For the latest information on SPCC requirements and compliance deadlines, visit the EPA's website at:

<http://www.epa.gov/oilspill/index.htm>

Universal Waste

Universal wastes are wastes that meet hazardous waste criteria but, because they pose a relatively low-risk compared to other hazardous wastes and are generated by a wide variety and large number of businesses, are exempt from regulation as hazardous waste.

Although universal wastes are exempt from the hazardous waste regulations of Subchapters 1 through 7 of the Vermont Hazardous Waste Management Regulations (VHWMR), they still must be managed according to the Subchapter 9 Universal Waste Management Standards. Wastes that can be managed as universal waste in Vermont include: **BATTERIES, CERTAIN PESTICIDES, MERCURY THERMOSTATS, PCB-CONTAINING FLUORESCENT LIGHT BALLASTS, LAMPS** (e.g., fluorescent bulbs), **MERCURY-CONTAINING DEVICES** (e.g., mercury switches), **AND CATHODE RAY TUBES** (e.g., color computer monitors and TV screens).

In general, the Universal Waste Management Standards include requirements that apply to small and large quantity “handlers” of universal waste (including specific management standards for each category of universal waste), “universal waste transporters,” and “destination facilities.” However, since the vast majority of the Vermont businesses that manage universal waste fall into the “small quantity handler” category, this Fact Sheet focuses primarily on those requirements.

What is a Small Quantity Handler?

A **“UNIVERSAL WASTE HANDLER”** is defined as:

1. A generator of universal waste; or
2. The owner or operator of a facility, including all contiguous property, that receives universal waste from other universal waste handlers, accumulates universal waste, and sends universal waste to another universal waste handler, to a destination facility, or to a foreign destination.

A **“SMALL QUANTITY HANDLER”** is defined as:

A universal waste handler who does not accumulate 5,000 kilograms (11,000 pounds) or more total of universal waste other than CRTs (batteries, pesticides, thermostats, ballasts, lamps, or mercury-containing devices, calculated collectively), and who does not accumulate 36,288 kilograms (40 tons) or more of CRTs, at any time.

What does a Small Quantity Handler need to comply with?

Although **EACH CATEGORY OF UNIVERSAL WASTE HAS UNIQUE WASTE MANAGEMENT REQUIREMENTS** (individual Fact Sheets are available for lamps, mercury-containing devices and CRTs), small quantity handlers must manage all universal wastes according to the following general requirements:

- Manage universal wastes in a way that prevents breakage and releases to the environment.
- Keep containers of universal waste closed.
- Immediately contain and transfer any universal wastes that show evidence of leakage or damage to an appropriate container.
- Meet waste-specific container or packaging requirements.
- Label or mark the universal waste (or container holding the universal waste) to indicate that it is a waste or universal waste. For example, universal waste lamps should be marked as “Universal Waste Lamps,” “Waste Lamps,” or “Used Lamps.”
- Accumulate universal waste for no longer than one year (a handler must be able to demonstrate the length of time that a universal waste has been accumulated from the date it became a waste or is received).
- Ensure that employees handling universal waste are familiar with proper handling and emergency procedures, relative to their responsibilities.
- In the event of a release of universal waste, comply with the emergency actions and reporting requirements of VHWMR Section 7-105(a), and determine if any material resulting from the release is hazardous waste.

Where can Small Quantity Handlers bring Universal Waste?

Small quantity handlers can bring their universal wastes to another universal waste handler or a destination facility (which, in general, is defined as *a facility that treats, disposes of, or recycles a particular category of universal waste*). Small quantity handlers may also send universal waste to a foreign destination provided the specific export requirements of VHWMR Section 7-912(k) are met.

Who can Transport Universal Waste?

Small quantity handlers can either self-transport their own universal waste or hire a commercial transporter. Anyone that transports universal waste must comply with applicable Federal Department of Transportation requirements and, if using a vehicle with a gross vehicle weight greater than one ton, with the solid waste permit requirements of 10 V.S.A. § 6607a. No hazardous waste manifest shipping document is required for the transport of universal waste.

Used Oil

What is used oil and how is it regulated?

Used oil is defined as any petroleum product refined from crude oil or any synthetic oil that has been used and has been contaminated as a result of that use. Used oil is a free-flowing liquid at standard temperature and pressure and has a flash point greater than 100 degrees F.

The term “used oil” does not include fuels or solvents but may include:

- Vehicle crankcase oils, transmission fluids and power steering fluids;
- Hydraulic, compressor and straight cutting oils;
- Tramp oil and oil drained from evaporators.

Used oil is regulated under the Used Oil Management Standards of Subchapter 8 of the Vermont Hazardous Waste Management Regulations. Do-it-yourselfers who produce used oil are exempt from the Subchapter 8 standards.

What can be done with used oil?

- Send it off-site to be fuel-blended and burned for energy recovery *or* re-refined for reuse as a lubricant.
- Reuse it to lubricate chains, tools and other machinery. Don't let it drip on the ground.
- Burn it on-site in used oil space heating equipment (refer to FACT SHEET - FS3 “Burning Used Oil Fuel” for more information), **OR** give it away or sell it as fuel.
- Check with the Solid Waste District in your area to see if they have a collection program for small businesses.

What *cannot* be done with used oil?

- Used oil cannot be disposed of in a Vermont landfill.
- Used oil cannot be applied to roads for dust control.
- Used oil cannot be mixed with a hazardous waste, with the exception that used oil may be mixed with waste that is hazardous only because it exhibits the characteristic of ignitability (e.g., ignitable-only mineral spirits), provided the resultant mixture is not ignitable.

How should used oil be stored?

Used oil must be stored in containers that are:

- In good condition and made of or lined with compatible material;
- Kept closed except when adding or removing used oil;
- Labeled with the words “Used Oil;”
- Located on an impervious surface (like concrete or asphalt); and
- Within a structure that sheds rain and snow.

Used oil must be stored in above-ground tanks that are:

- Installed and operated in accordance with Vermont Department of Labor and Industry standards;
- Labeled with the words “Used Oil;”
- Managed in a manner so as to prevent a release to the environment; and
- If located out-doors, equipped with secondary containment capable of holding the contents of the tank.

A PERMIT IS REQUIRED TO STORE USED OIL IN AN UNDERGROUND STORAGE TANK (UST). CONTACT VERMONT’S UST PROGRAM AT 802-828-1138 FOR ASSISTANCE.

How Can Used Oil be Transported?

Used oil generators can self-transport their own used oil without obtaining a transporter permit provided:

- No more than 55 gallons are transported at any one time;
- Containers meet Federal Department of Transportation standards; and
- Used oil is transported in a vehicle owned by the generator or an employee.

To transport more than 55 gallons of used oil at one time, contact the Waste Management Division to obtain either a list of permitted hazardous waste transporters, or a hazardous waste transporter permit application.

What else do I need to know?

Notification: Facilities that generate used oil, but don’t generate any hazardous waste and don’t accept used oil from off-site, are not required to notify. Most facilities that manage used oil do, however, generate some hazardous waste (e.g., oily sorbent or debris) and therefore must notify the Waste Management Division of its hazardous waste activity using the **VERMONT WASTE HANDLER SITE ID FORM** (available on-line or from the Division). Facilities that accept used oil from off-site must notify as a used oil collection facility.

Hazardous waste generator status: Facilities that generate both used oil and hazardous waste should not count the volume of used oil generated when calculating hazardous waste generator status (based on the amount of hazardous waste generated each month). If a business *chooses* to manage used oil as hazardous waste (i.e., under the VT02 hazardous waste code), the business would need to count that waste toward its generator status.

USED OIL - FS22

Hazardous waste manifest: A hazardous waste manifest shipping document *is not required* when transporting used oil. If a business chooses to ship used oil using a manifest, or if a hired transporter requires the use of a manifest, the used oil should be identified on the manifest using the VT99 code for non-hazardous waste. Finally, if a business *chooses* to manage used oil as hazardous waste (i.e., under the VT02 hazardous waste code), the business would need to ship the used oil using a manifest.

Federal planning requirements: The U.S. EPA requires a Spill Prevention, Control and Countermeasure (SPCC) plan for any facility that has above-ground petroleum storage capacity exceeding 1,320 gallons (refer to FACT SHEET - FS20 “Federal Spill Prevention, Control, and Countermeasure Regulation” for more information).

Washwater Discharges From Vehicle Washing

Water used in washing cars, trucks, and other equipment may contain a wide range of contaminants including oil, other hydrocarbons, metals, detergents, road salt, and grit. These pollutants can be toxic and harmful to living organisms, including fish and the people who eat the fish. It is important to keep these contaminants out of our surface and drinking water. **THE DEPARTMENT OF ENVIRONMENTAL CONSERVATION'S (DEC) POLICY** (dated 12/09/02) **COVERS ONLY THE WASHWATER GENERATED FROM WASHING THE EXTERIOR OF VEHICLES** (cars, trucks, buses, and light or heavy equipment). It supersedes the parts of the "DEC's Floor Drain Procedure" (signed October 8, 1993) that refer to vehicle washing.

There are four options for handling your vehicle washwater:

1. Install a closed system with no discharge

Operate a "closed loop system" by recycling your washwater. Because no wastewater is discharged to the ground's subsurface or surface, this would not require a UIC permit. However, if it includes a holding tank, the tank will need to be permitted by the DEC Regional Office in your area.

2. Install a holding tank

Install a holding tank to collect the washwater from the floor drain and have the contents disposed of properly. Holding tanks can be installed and pumped out as needed by a qualified hauler. The holding tank contents must be disposed of at an approved disposal facility (i.e., a municipal wastewater treatment facility). Holding tanks require a permit from the DEC Regional Wastewater Office in your area (see contact info in Appendix D - Regional Office Map). The town may also need to approve the disposal at its wastewater treatment facility.

3. Discharge to municipal sanitary sewer

Connections to the local wastewater treatment facility must be permitted by the Regional Offices and may require adequate pretreatment (e.g., an oil/water separator). The town may also have an approval process for connections to its wastewater treatment facility.

4. Limit washings to 30 or fewer vehicles per week

If the following conditions are met, the washwater from 30 or fewer vehicle washings per week may be discharged to the **GROUND SURFACE**.

- B. Whether these vehicle washings occur indoors or outside, the following conditions must be met:

WASHWATER DISCHARGES FROM VEHICLE WASHING - FS23

- i. The washwater going to the ground surface must sheet flow over a vegetated area and infiltrate or evaporate on-site, therefore the site should not be graded in a way that encourages the collection of the washwater.
 - ii. The washwater must not cause soil erosion and must not reach waters of the state, either directly or through stormwater drains or ditches.
 - iii. Only non-phosphorus soaps may be used.
 - iv. The use of acids, bases, metal brighteners and degreasing agents as well as pressure washing engines, undercarriage washing and engine cleaning are all prohibited.
- B. If the vehicle washing takes place indoors (discharging to ground surface), the following **ADDITIONAL** conditions must be met:
- i. All washing must occur in a wash bay that has a floor drain and is physically separated from where vehicles are serviced.
 - ii. An oil-water separator must be installed on the floor drain piping.
 - iii. The floor drain must be registered with the UIC program (call the UIC Program, 802-828-1535).
 - iv. Hazardous materials can't be stored in the wash area unless adequate containment is provided.
- B. If the vehicle washing takes place outside; the following **ADDITIONAL** conditions must be met:
- i. Whenever possible, the washing should occur on an impermeable surface (i.e., concrete, asphalt, plastic, or other) and then sheet flow over a vegetated area.

Regardless of which option you chose, remember:

IF THERE IS EVER A HAZARDOUS SPILL TO A FLOOR DRAIN OR TO THE GROUND AND THERE IS A POTENTIAL FOR GROUNDWATER CONTAMINATION OR THE CONTENTS OF A HOLDING TANK IS IN QUESTION, CONTACT THE HAZARDOUS SPILLS HOTLINE 800-641-5005 FOR ASSISTANCE.

Waste Motor Vehicle Fuel and System Components

This Fact Sheet covers management options for businesses that handle gasoline and diesel fuel removed from motor vehicles and waste fuel system components such as tanks, lines and filters.

Fuel that can be reused as fuel is not considered a hazardous waste. Contaminated fuel that cannot be reused as fuel is regulated under the Vermont Hazardous Waste Management Regulations (VHWMR) as discussed below.

What can I do with uncontaminated fuel that has been removed from a motor vehicle?

Uncontaminated fuel should be returned to the vehicle from which it was removed or otherwise used as motor fuel whenever possible. Fuel that is stored temporarily should be stored in a container that is:

- In good condition and compatible with the fuel;
- Clearly labeled to identify its contents;
- Kept closed and located on an impervious surface, away from floor drains; and
- Grounded, if necessary.

How do I manage contaminated fuel?

Contaminated *gasoline* that cannot be reused as fuel is regulated as hazardous waste because it is ignitable (i.e., has a flash point less than 140 degrees F) (hazardous waste code D001) and contains toxic constituents such as benzene (hazardous waste code D018).

Contaminated *diesel* fuel may be:

- Used as a lesser grade fuel to be burned for energy recovery; or
- Managed as “used oil” (refer to FACT SHEET - FS22 “Used Oil” for more information on used oil management standards); or
- Mixed with used oil provided the resulting mixture is not ignitable; or
- Managed as hazardous waste.

What else should I know about managing contaminated fuel?

- **DO NOT MIX WASTE GASOLINE WITH USED OIL.** Gasoline contains benzene and other toxic constituents that can easily cause used oil to become regulated as hazardous waste.

- **DO NOT ALLOW WASTE FUEL TO EVAPORATE.** The evaporation of waste fuel not only introduces harmful vapors into the air, but also is considered illegal disposal of a hazardous waste.
- **USED ABSORBENT MATERIALS (E.G., PADS, GRANULAR PRODUCTS) GENERALLY MUST BE MANAGED AS A HAZARDOUS WASTE** and cannot be discarded with solid waste. See the FACT SHEET - FS14 “Oily Wastes” for more information.

How should waste fuel filters (and other components) be managed?

Fuel filters: Due to the fact that the filter media within fuel filters typically retains residual fuel after draining, used filters may be considered hazardous waste. Because section 7-204(e) of the VHWMR provides an exemption for scrap metal that is recycled, metal filters that have been drained are not regulated as hazardous waste so long as they are recycled as scrap. Metal-encased fuel filters that are not recycled as scrap metal must be managed as hazardous waste. Since there is no such exemption for plastic fuel filters, they must be managed as hazardous waste.

Used fuel system components that are to be discarded, such as fuel lines and tanks, must be drained of fuel. Metal components may be managed as scrap metal. Non-metal components that have been drained, with the exception of fuel filters or other absorbent components, may be managed as non-hazardous waste.



WHAT ARE SOME BEST MANAGEMENT PRACTICES?

- Always store flammable materials away from ignition sources such as stoves and welding equipment.
- Use drip pans to minimize the need for absorbents.
- If fuel must be removed from a vehicle, collect it in a manner to ensure that it is not contaminated.

Appendices

APPENDICES

Appendix A	Common OSHA Violations for Vehicle Service Shops.....	91
Appendix B	Hazardous Chemical Decision Diagram for Tier II Reporting.....	93
Appendix C	Vermont Solid Waste Management Entities	94
Appendix D	Regional Office Map	95
Appendix E	Permit and License Information (new construction or existing)	96
Appendix F	Common Listed and Characteristic Hazardous Waste.....	98
Appendix G	Procedure Addressing the Management and Disposal of Aerosol Cans	100
Appendix H	VT Hazardous Waste Handler Site ID Form Example	104
Appendix I	Hazardous Waste Compatibility List.....	107
Appendix J	Hazardous Waste Manifest Information & Form Example	109

Common OSHA Violations for Vehicle Service Shops

The following list describes 10 of the most violations cited by the U.S. Department of Labor for the Autobody Industry (SIC 7532) listed in order of the most to least common violation. OSHA 29 CFR (Code of Federal Regulations) addresses General Industry Standards.

1. Respiratory Protection. 29 CFR 1910.134

Your shop is required to have a written respiratory plan. All employees wearing respiratory equipment must be fit tested annually, you must provide medical clearance and screening, and provide training to all employees exposed to respiratory exposures.

2. Hazard Communication. 29 CFR 1910.1200

Your shop is required to have a written hazard communication (haz-com) program, maintain Safety Data Sheets (SDS) for each chemical (and a list of all chemicals), label all products, and provide haz-com training to all employees directly involved with chemical handling.

3. Spray Finishing Using Flammable and Combustible Materials. 29 CFR 1910.107

This OSHA requirement focuses primarily on the spray booth operation or areas where dangerous quantities of flammable vapors or mists, or combustible residues, dusts, or deposits are present due to the operation of spraying processes.

4. Wiring Methods, Components, and Equipment for General Use. 29 CFR 1910.305

This section deals with the general electrical system at your facility including wiring, your electric panel, and your general electricity service at the facility.

5. Lead. 29 CFR 1910.1025

This section applies to all occupational exposures to lead. You must have an adequate employee exposure monitoring program in place including baseline as well as regular exposure information.

(NOTE: *This section does not apply if you do not have employee exposure to lead.*)

6. Portable Fire Extinguishers. 29 CFR 1910.157

The requirements of this section apply to the placement, use, maintenance, and testing of portable fire extinguishers provided for the use of employees. You must provide monthly fire extinguisher checks, including an annual check, as well as provide employee training on fire extinguisher use.

7. General Requirements. 29 CFR 1910.303

This requirement focuses primarily on electrical equipment and the associated wiring and electrical connections to the electrical system at your facility.

8. General Requirements. 29 CFR 1910. 132

This section focuses on protective equipment, including personal protective equipment for eyes, face, head, and extremities, protective clothing, respiratory devices, and protective shields and barriers. It also requires you to conduct a PPE assessment for each job task.

9. Flammable and Combustible Liquids. 29 CFR 1910.0106


This section covers a wide range of topics dealing with flammable and combustible liquids ranging from pressure vessels to the storage of liquids in tanks, including the proper installation, setbacks, and other specifics dealing with both above and below ground tanks.

10. Abrasive Wheel Machinery. 29 CFR 1910.0215


This section focuses on what is required for the use of abrasive wheel grinders and other abrasive wheel machinery. For grinders they must be properly guarded and the tool rest should be securely fastened $\frac{1}{8}$ of an inch from the grinding wheel surface, and remember to keep the top debris guard $\frac{1}{4}$ inch from the wheel surface. The section covers all kinds of grinding.

Hazardous Chemical Decision Diagram for Tier II Reporting

VERMONT Hazardous Chemical Inventory Reporting Decision Diagram



Vermont Solid Waste Management Entities



Regional Office Map

Department of Environmental Conservation (DEC) District Environmental Commissions (Act 250)

Districts 1, 8, & 9*

450 Asa Bloomer State Office Bldg., Merchants Row,
Rutland, VT 05701-5903

DEC Permit Specialist	282-6488
DEC Water/Wastewater Program	786-5900
Act 250 (Dist #1 & 8)	786-5920
Act 250 (Dist #9)	879-5614

Districts 2 & 3

100 Mineral Street, Suite #303, Springfield, VT 05156

DEC Permit Specialist	279-4747
DEC Water/Wastewater Program	885-8956
Act 250 (Dist #2 & #3)	885-8846 or 885-8840

Districts 4 & 6

111 West Street, Essex Junction, VT 05452

DEC Permit Specialist	477-2241
DEC Water/Wastewater Program (Dist #4 & 6)	879-5656
Act 250 (Dist #4 & 6)	879-5614

Districts 3A* & 5

5 Perry Street, Suite 80, Barre, VT 05641-4282

DEC Permit Specialist	505-5367
DEC Water/Wastewater Program	476-0189
Act 250 (Dist # 3 & 3A)	885-8843
Act 250 (Dist # 5)	476-0185


District 7

1229 Portland Street, Suite 201, St. Johnsbury, VT 05819

DEC Permit Specialist (Tuesday)	505-5367
DEC Water/Wastewater Program	751-0130
Act 250	751-0120

3A* NOTE: For towns in District 3A, contact the Springfield Office for Act 250 Permits. For water/wastewater permits and Subdivision Approval, District 3A should contact the Barre Office.

9* NOTE: For towns in District 9, contact the Essex Junction Office for Act 250 Permits. For water/wastewater permits and Subdivision Approval, District 9 should contact the Rutland Office.



Permit and License Information

Several state permits and licenses may be required to operate an auto repair garage or service station, whether it is in a new or existing building. Permits are also required if you operate the facility as a home occupation. Often times modifications to existing facilities trigger the need for a permit that perhaps was not there until the modification took place.

The Department of Environmental Conservation provides a unique service to anyone with questions about state permits. Vermont Permit Specialists are located in our four regional offices including Springfield, Essex Junction, Rutland, and Barre, as well as part time in satellite offices in St. Johnsbury, St. Albans, Bennington, Middlebury, and Morrisville. Call them at the numbers listed in Appendix L. They will guide you through the process by completing a Project Review Sheet that identifies state permits or licenses that your project may need. It could save you time, money, and headaches. You can determine which permit specialist serves your area on-line by searching key words ‘Vermont Permit Specialist.’

Department Of Environmental Conservation

- **Wastewater System & Potable Water Supply Permit** may be required whether or not your garage has a water supply or septic system. If you operate your garage on the same property as your residence, it may qualify for an exemption as a home occupation provided you have no employees other than family members, and there is no general public access. If you have employees, sanitary facilities may have to be provided. You may have to hire a Vermont licensed designer to design a water source and septic system or connection to municipal water and sewer. Please contact a Wastewater Management Division Regional Engineer to discuss your particular requirements. Essex: 802-879-5656; Rutland: 802-786-5900; Springfield: 802-885-8855; St Johnsbury: 802-751-0130

Floor Drains are prohibited in vehicle service areas unless they are approved by the Wastewater Management Division and the municipality for connection to municipal sewer. Floor drains connected to leach fields or dry wells present a high level of risk of contamination of ground water from even a small spill of oil, gasoline or solvents.

For more information or if you have questions concerning alternatives to floor drains, please contact a Wastewater Management Regional Engineer (see phone numbers above).

- **Management of Hazardous Wastes** such as used oil, burning of used oil, used antifreeze, waste solvents, waste paints, etc., are regulated by the DEC Waste Management Division. Anyone who generates hazardous waste must complete a Hazardous Waste Handler Site ID Form. No fee is required. See sample form in Appendix H. Instructions are available on-line by searching key words ‘Vermont Waste Handler Site ID Instructions’.

PERMIT AND LICENSE INFORMATION

- **Underground Storage Tanks** for petroleum product and waste oil are required to be permitted. For more information contact the Underground Storage Tank (UST) program at 802-828-1138.
- **Air Pollution Control.** Autobody shops and vehicle repair operations are required to comply with air pollution regulations. Contact the Air Quality and Control Division at 802-828-1288 for more information.
- **Environmental Assistance Division** provides free, voluntary, confidential assistance concerning DEC regulations. Advice is also available about new technologies, recycling opportunities, and methods to reduce the amount of wastes you produce. Plain English guide books have been produced for both the autobody and vehicle service sectors. They are available on-line and in hard copy. For more information call 800-974-9559.

District Environmental Commission (Act 250): <http://www.nrb.state.vt.us>

Construction of improvements for commercial purposes may require an Act 250 permit. Contact the Act 250 District Coordinator at the Regional Environmental Office for a jurisdictional ruling on your specific project.

Department of Public Safety, Division of Fire Safety: <http://firesafety.vermont.gov/>

The Division of Fire Safety has jurisdiction over any public building. This department reviews projects with respect to issues of fire safety, building codes, accessibility, boiler inspections, and electrical and plumbing installations.

District Division of Fire Safety Offices:

Barre: 802-479-4434

Rutland: 802-786-5867

Springfield: 802-885-8883

Williston: 802-879-2300

Other Government Offices You Should Contact:

- Local municipal offices regarding zoning permits and sewer use ordinance
- Vermont Department of Taxes
- Secretary of State
- Agency of Agriculture, Food and Markets (gas pumps)

This is not an all-inclusive list, but identifies the permits and licenses that are most likely required prior to operating an autobody shop or vehicle service facility.

Common Listed and Characteristic Hazardous Waste

Subchapter 2 of the Vermont Hazardous Waste Management Regulations (VHWMR) identifies all of the wastes that are regulated as hazardous wastes in Vermont.

“F-Listed” Hazardous Wastes:

Refer to the VHWMR Section 7-210 for the complete list of wastes from non-specific sources.

- F001** The following spent halogenated solvents used in degreasing: Tetrachloroethylene, trichloroethylene, methylene chloride, 1,1,1-trichloroethane, carbon tetrachloride, and chlorinated fluorocarbons. Also still bottoms from these spent solvents and solvent mixtures.
- F002** The following spent halogenated solvents: Tetrachloroethylene, methylene chloride, trichloroethylene, 1,1,1-trichloroethane, chlorobenzene, 1,1,2-trichloro-1,2,2-trifluoro-ethane, orthodichlorobenzene, trichlorofluoromethane, and 1,1,2-trichloroethane. Also still bottoms from these spent solvents and solvent mixtures.
- F003** The following spent non-halogenated solvents: Xylene, acetone, ethyl acetate, ethyl benzene, ethyl ether, methyl isobutyl ketone, n-butyl alcohol, cyclohexanone, and methanol. Also still bottoms from these spent solvents and solvent mixtures.
- F005** The following spent non-halogenated solvents: Toluene, methyl ethyl ketone, carbon disulfide, isobutanol, pyridine, benzene, and 2-nitropropane. Also still bottoms from these spent solvents and solvent mixtures.
- F006** Wastewater treatment sludges from electroplating operations except from the following processes: (1) sulfuric acid anodizing of aluminum; (2) tin plating on carbon steel; (3) zinc plating (segregated basis) on carbon steel; (4) aluminum or zinc-aluminum plating on carbon steel; (5) cleaning/stripping associated with tin, zinc, and aluminum plating of carbon steel; and (6) chemical etching and milling of aluminum.
- F007 through F012** Various plating wastes where cyanides are used.
- F032** Wastewaters, process residuals, preservative drippage, and spent formulations from wood preserving processes generated at plants that currently use or have previously used chlorophenolic formulations (unless the generator meets all requirements of 40 CFR Section 261.35).
- F034** Wastewaters, process residuals, preservative drippage, and spent formulations from wood preserving processes generated at plants that use creosote formulations.
- F035** Wastewaters, process residuals, preservative drippage, and spent formulations from wood preserving generated at plants that use inorganic preservatives containing arsenic or chromium.

“VT-Listed” Hazardous Wastes:

- VT01** Wastes containing PCBs in concentrations equal to or greater than 50 parts per million.
- VT02** Waste containing greater than 5% by weight of petroleum distillates with melting points of less than 100° F, including but not limited to kerosene, fuel oil, hydraulic oils, lubricating oils, penetrating oils, tramp oils, quenching oils, and crankcase and automotive oils.
- VT03** Wastewater-miscible metal cutting and grinding fluid.
- VT06** Pesticidal wastes and obsolete pesticidal products not specifically listed in Subchapter 2 of the Regulations.
- VT08** Waste ethylene glycol and solutions containing greater than 700 parts per million (ppm) of ethylene glycol (e.g., coolants, antifreeze).
- VT20** A solid material that when mixed with an equal weight of distilled water causes the liquid fraction of the mixture to exhibit the properties of the corrosivity characteristic as specified in § 7-206(a)(3) of the Regulations.
- VT99** Non-hazardous waste. This code is to be used only for non-hazardous waste shipped using a hazardous waste manifest.

Characteristic Hazardous Wastes:

Refer to the VHWMR Sections 7-205 through 7-208 for complete descriptions of each hazardous waste characteristic.

- D001** (Ignitable waste): Liquid with a flash point of less than ~140° F; or is not a liquid and is capable under standard temperature and pressure of causing fire and creating a burning hazard; or is an ignitable compressed gas; or is an oxidizer (the chemical names of oxidizers often have “per” as a prefix, “ate” as a suffix, or include “oxide”).
- D002** (Corrosive waste): Liquid with a pH < 2 or ≥ 12.5; or that corrodes steel at a rate greater than 1/4 inch/year.
- D003** (Reactive waste): Waste that is unstable; reacts violently with water; can generate toxic gases; or is capable of detonation.
- D004 through D043** (Toxicity Characteristic wastes): Wastes that when analyzed using the “Toxicity Characteristic Leaching Procedure” (TCLP) are found to contain any of the following contaminants at concentrations (in milligrams per liter) greater than or equal to the value identified in parentheses.
- | | |
|-----------------------------------|--|
| D004 - Arsenic (5.0 mg/l) | D019 - Carbon tetrachloride (0.5 mg/l) |
| D005 - Barium (100.0 mg/l) | D022 - Chloroform (6.0 mg/l) |
| D006 - Cadmium (1.0 mg/l) | D023 through D026 - Cresols (200 mg/l) |
| D007 - Chromium (5.0 mg/l) | D035 - Methyl ethyl ketone (200.0 mg/l) |
| D008 - Lead (5.0 mg/l) | D037 - Pentachlorophenol (100.0 mg/l) |
| D009 - Mercury (0.2 mg/l) | D039 - Tetrachloroethylene (0.7 mg/l) |
| D011 - Silver (5.0 mg/l) | D040 - Trichloroethylene (0.5 mg/l) |
| D018 - Benzene (0.5 mg/l) | D043 - Vinyl Chloride (0.2 mg/l) |

Procedure Addressing the Management and Disposal of Aerosol Cans

§ 1. PURPOSE AND AUTHORITY

- (a) Purpose. This technical guidance document describes allowable management options for waste aerosol cans generated by typical industrial and commercial applications; it does not address management and disposal options for household-generated aerosol cans. Homeowners are encouraged to contact your Solid Waste District for information on environmentally responsible disposal.
- (b) Authority. This procedure was adopted under the Vermont Hazardous Waste Management Regulations (VHWMR) and is an explanation of a generator's obligations when treating or disposing of empty or partially empty aerosol cans that may contain hazardous waste.

§ 2. BACKGROUND

Waste aerosol cans consist of three types of materials:

(1) the metal can, (2) the "product" contained in the can, and (3) the propellant. Residual product or propellant (or both) may cause a can to be regulated as hazardous waste under the VHWMR, and it is the responsibility of the generator of the waste to make that determination. See FACT SHEET - FS5 "Making a Hazardous Waste Determination" for more information.

Store aerosol cans that are hazardous waste in a separate container from that used to store non-hazardous waste cans.

§ 3. EMPTY AEROSOL CANS

- (a) For the purposes of the VHWMR, aerosol cans are considered **EMPTY** when:
 - The product has been expelled from the can and only residue remains; **AND**
 - The pressure in the can is at or very near atmospheric pressure at normal room temperature.
- (b) Once a can is empty, it can be disposed of in the regular trash or, preferably, recycled as scrap metal **UNLESS** it contained a P-listed chemical. Any aerosol can that contained a P-listed chemical **MUST** be managed as hazardous waste even when empty (see VHWMR Section 7-215).
- (c) Empty aerosol cans shall be stored separately from partially full or full hazardous waste aerosol cans. Puncturing of empty aerosol cans in accordance with the requirements of Sections 6 and 7 of this procedure is acceptable.

§ 4. NON-HAZARDOUS PRODUCTS/PROPELLANT

Waste aerosol cans that contain non-hazardous products and propellant may be disposed of in the regular trash. However, in some instances, cans containing non-hazardous product and/or propellant may still exhibit the hazardous waste characteristic of reactivity (see VHWMR Section 7-207), typically because of the potential to explode when subjected to heat or other initiating source. Each generator must consider whether or not a waste aerosol can is a reactive hazardous waste using their knowledge of the product (a generator may refer to the product label, SDS, or other product information to assist with the waste determination).

Waste aerosol cans that contain non-hazardous product and propellant should be stored separately from partially-full or full hazardous waste aerosol cans. Puncturing of non-hazardous aerosol cans is acceptable.

§ 5. HAZARDOUS PRODUCTS AND PROPELLANT

(a) A partially-full or full discarded aerosol can is a hazardous waste if the can contains:

- A product or propellant that exhibits one or more of the characteristics of ignitability, corrosively, reactivity, or toxicity; and/or
- A U-listed chemical (see VHWMR Appendix III); or
- A P-listed chemical or the residue of a P-listed chemical (see VHWMR Appendix IV)

NOTE: *Each generator must determine if waste aerosol cans exhibit the hazardous waste characteristic of reactivity using their knowledge of the product and propellant.*

(b) Pesticides, Herbicides, and Rodenticides

Aerosol cans that contain pesticides, herbicides, or rodenticides are regulated in Vermont by the Agency of Agriculture, Food and Markets and the Federal Insecticide, Fungicide, and Rodenticide Act (FIRFA). Follow the manufacturer's instructions on proper disposal.

§ 6. USE OF AEROSOL CAN PUNCTURING DEVICES

Waste aerosol cans that are full, partially full or empty may be punctured to make them more amenable to recycling as scrap metal. If, prior to puncturing, the can is regulated as hazardous waste (i.e., exhibits a characteristic or is listed), the puncturing and draining of those cans is considered **"GENERATOR TREATMENT"** of hazardous waste. VHWMR Section 7-502(o) requires all generators to notify the Secretary about their hazardous waste treatment process(es). A form for such notification can be found online by searching key words 'Vermont generator treatment form'.

§ 7. AEROSOL CAN PUNCTURING CONDITIONS

- (a) The puncturing, waste collection, and disposal of aerosol cans and the collected residuals must be conducted in compliance with all applicable federal, state, and local waste (solid and hazardous waste) and occupational safety and health laws and regulations.
- (b) If you choose to treat (puncture) full or partially-full aerosol cans that are hazardous waste, the following conditions must be met:
- (1) The generator notifies the DEC of their treatment of hazardous waste;
 - (2) The device is designed for the purpose of puncturing aerosol cans and is protective of human health and the environment;

PROCEDURE ADDRESSING THE MANAGEMENT AND DISPOSAL OF AEROSOL CANS

- (3) The device is operated in accordance with all manufacturer specifications/recommendations;
- (4) All materials released upon puncturing are captured — liquid and vapors (i.e., must be equipped with a VOC filter and/or other pollution prevention device);
- (5) The device is affixed to a collection container that is managed, marked and labeled in accordance with the container management requirements of VHWMR 7-310 and 7-311;
- (6) All residual liquids and vapor are compatible with each other and the container. If compatibility is a concern, a generator should use multiple containers to collect process residuals (e.g., one drum for aerosol lubricants, one drum for paints, one drum for chlorinated solvent aerosols);
- (7) The collection container is kept closed unless adding or removing waste. A drum with an affixed puncturing device is considered closed if the puncturing device lid is closed and secured and a VOC filter is in place; The generator develops a company-specific procedure that specifies:
 - (A) What type(s) of waste aerosol cans are being punctured (i.e., materials contained/ type of propellant) to ensure compatibility of collected residuals and identify potential reactivity;
 - (B) A schedule/procedure for maintaining the puncturing/treatment equipment and air pollution control device;
- (8) The generator ensures that collected residuals are properly characterized, maintains a log that identifies the material contained in each can together with the date of treatment and the person conducting the treatment.

NOTE: *The appropriate waste codes and identification of underlying hazardous constituents (used to meet LDR requirements) may be identified from this log;*

- (9) Collected residuals are managed and disposed of as hazardous waste;
- (10) A hazardous waste determination is completed for the spent VOC filter (used for pollution control) prior to disposal of the filter (i.e., by generator knowledge or test for any hazardous waste toxicity characteristic constituents that are present in the products collected from the aerosol cans);
- (11) The generator ensures that all personnel operating the puncturing device have been trained in the proper operation of the equipment and the company-specific procedure. Training of personnel to operate the equipment must be documented.

NOTE: *Aerosol cans of P-listed waste cannot be punctured and must be disposed of as hazardous waste.*


- (c) Generators may accumulate waste cans prior to puncturing/treatment for up to one year in accordance with VHWMR 7-310(a) or (b).
- (d) The Vermont Department of Environmental Conservation does not provide any type of certification, approval or endorsement regarding the design, use, and safety of aerosol can puncturing equipment.

§ 8. CONTAINERS OF AEROSOL CANS AFTER PUNCTURING

After cans have been punctured and drained in accordance with this guidance document, they may be discarded as solid waste or recycled as scrap metal. The DEC recommends that punctured aerosol cans be recycled.

§ 9. Effective Date - 10/5/2011

PROCEDURE ADDRESSING THE MANAGEMENT AND DISPOSAL OF AEROSOL CANS



^[1] Aerosol cans are considered empty when the product has been expelled from the can and only residue remains and the pressure in the can is at or very near atmospheric pressure at normal room temperature.
^[2] For information concerning puncturing, see Aerosol Can Puncturing Conditions.

VT Hazardous Waste Handler Site ID Form Example

 VERMONT VT HAZARDOUS WASTE HANDLER SITE ID FORM Please return completed form to: VT DEC Waste Management & Prevention Division One National Life Drive, Davis 1 Montpelier, Vermont 05620-3704 www.anr.state.vt.us/dec/wastediv/rcra/rcrahome.htm 802-828-1138		Shaded box for VT DEC Office Use Only Date In: Date Complete:
1. Reason for Submittal Mark Correct Box(es)	<input checked="" type="checkbox"/> To provide initial notification (to obtain an EPA ID Number for hazardous waste, including used oil, or universal waste activities). <input type="checkbox"/> To provide subsequent notification (to update site identification information). Reason: _____	
2. Site EPA ID	EPA ID Number:	
3. Site Name	Name: Acme Auto Service	
4. Site Location Information	Street Address (not P.O. Box): 9999 South Main Street City or Town: Waterbury State: VT County Name: Washington Zip Code: 05123	
5. Site Land Type	<input checked="" type="checkbox"/> Private <input type="checkbox"/> County <input type="checkbox"/> District <input type="checkbox"/> Federal <input type="checkbox"/> Tribal <input type="checkbox"/> Municipal <input type="checkbox"/> State <input type="checkbox"/> Other	
6. NAICS Code(s) for Site <small>http://www.census.gov/eos/www/naics/</small>	A. 811111	B.
	C.	D.
7. Site Mailing Address	Number and Street or P. O. Box: <input type="checkbox"/> Same as 4, above or: P.O. Box 99999 City or Town: Waterbury State: VT Country: USA Zip Code: 05123-99999	
8. Site Contact Person	First Name: Will Last Name: Greene Title: Service Manager Street or P.O. Box: --Same as mailing above-- City: State: Zip Code: Country:	Phone Number w/ extension: 802-555-1212 Email address: will.b.greene@acmeauto.com
9. Legal Owner and Operator of the Site	Name of Site's Legal Owner: Acme Enterprises, LLC Date Became Owner (mm/dd/yyyy): 07/01/2000 Street or P.O. Box: P.O. Box 99999 City: Waterbury State: VT Zip Code: 05123-99999 Country: USA Phone: 802-555-1200	
(List additional owners or operators in Item 13-Comments)	Owner Type: <input checked="" type="checkbox"/> Private <input type="checkbox"/> County <input type="checkbox"/> District <input type="checkbox"/> Federal <input type="checkbox"/> Tribal <input type="checkbox"/> Municipal <input type="checkbox"/> State <input type="checkbox"/> Other Name of Site's Operator: Acme Auto Repair Date Became Operator (mm/dd/yyyy): 07/01/2012 Operator Type: <input checked="" type="checkbox"/> Private <input type="checkbox"/> County <input type="checkbox"/> District <input type="checkbox"/> Federal <input type="checkbox"/> Tribal <input type="checkbox"/> Municipal <input type="checkbox"/> State <input type="checkbox"/> Other	

	EPA ID No.
10. Type of Regulated Waste Activity (Mark 'X' in the appropriate boxes):	
A. Hazardous Waste Activities (check all that apply):	
<p>1. Generator of Hazardous Waste (Choose only one of the following three categories.)</p> <p><input type="checkbox"/> a. Large Quantity Generator (LQG): 2,200 lbs (1,000 kg) or greater of <i>non-acute</i> hazardous waste generated in a calendar month, or 2.2 lbs (1 kg) or greater of <i>acute</i> waste</p> <p><input type="checkbox"/> b. Small Quantity Generator (SQG): 220 - 2,200 lbs (100 to 1,000 kg) of <i>non-acute</i> hazardous waste and less than 2.2 lbs (1 kg) of acutely hazardous waste generated in a calendar month; and less than 13,200 lbs (6000 kg) accumulated</p> <p><input checked="" type="checkbox"/> c. Conditionally Exempt Generator (CEG): Less than 220 lbs (100 kg/mo) of <i>non-acute</i> hazardous waste and less than 2.2 lbs (1 kg) of acutely hazardous waste generated in a calendar month; and less than 2200 lbs (1000 kg) accumulated;</p> <p><input type="checkbox"/> 2. Short-term Generator (generate from a short-term or one-time event and not from an on-going process). If Yes, explain in the Comments Sect. 13</p>	
<p><input type="checkbox"/> 3. United States Importer of Hazardous Waste</p> <p><input type="checkbox"/> 4. Mixed Waste (hazardous and radioactive) Generator</p> <p><input type="checkbox"/> 5a. Transporter of Hazardous Waste Note: A hazardous waste transporter permit is required for this activity.</p> <p style="padding-left: 20px;"><input type="checkbox"/> 5b. Hazardous Waste Transfer Facility</p> <p><input type="checkbox"/> 6. Treater, Storer, or Disposer of Hazardous Waste (at your site) Note: A hazardous waste facility certification is required for this activity.</p> <p><input type="checkbox"/> 7. Recycler of Hazardous Waste (at your site) Note: A hazardous waste permit may be required for this activity.</p> <p><input type="checkbox"/> 8. Exempt Boiler and/or Industrial Furnace</p> <p style="padding-left: 20px;"><input type="checkbox"/> Small-Quantity On-site Burning Exemption</p> <p style="padding-left: 20px;"><input type="checkbox"/> Smelting, Melting, and Refining Furnace Exemption</p> <p><input type="checkbox"/> 9. SQG or LQG that receives waste from CEG owned/operated by same</p>	
<p>B. Universal Waste Activities:</p> <p><input type="checkbox"/> 1. Large Quantity Handler of Universal Waste (accumulate 11,000 lbs [5000 kg] or more) Mark all that apply:</p> <p style="padding-left: 20px;"><input type="checkbox"/> a. Batteries</p> <p style="padding-left: 20px;"><input type="checkbox"/> b. Lamps</p> <p style="padding-left: 20px;"><input type="checkbox"/> c. Pesticides</p> <p style="padding-left: 20px;"><input type="checkbox"/> d. Mercury-containing Devices</p> <p style="padding-left: 20px;"><input type="checkbox"/> e. Cathode Ray Tubes</p> <p style="padding-left: 20px;"><input type="checkbox"/> f. Mercury Thermostats</p> <p style="padding-left: 20px;"><input type="checkbox"/> g. PCB-containing Light Ballasts</p> <p><input type="checkbox"/> 2. Destination Facility for Universal Waste Note: A hazardous waste permit may be required for this activity.</p>	<p>C. Used Oil Activities:</p> <p>1. Used Oil Transporter - Indicate Type(s) of Activity(ies)</p> <p style="padding-left: 20px;"><input type="checkbox"/> a. Transporter</p> <p style="padding-left: 20px;"><input type="checkbox"/> b. Transfer Facility (at your site)</p> <p>2. Used Oil Processor and/or Re-refiner - Indicate Type(s) of Activity(ies)</p> <p style="padding-left: 20px;"><input type="checkbox"/> a. Processor</p> <p style="padding-left: 20px;"><input type="checkbox"/> b. Re-refiner</p> <p>3. Used Oil Burner</p> <p style="padding-left: 20px;"><input type="checkbox"/> a. Off-Specification</p> <p style="padding-left: 20px;"><input checked="" type="checkbox"/> b. Specification</p> <p style="padding-left: 20px;">If used oil is received from offsite, please list name & address of source _____</p> <p>4. Used Oil Marketer - Indicate Type(s) of Activity(ies)</p> <p style="padding-left: 20px;"><input type="checkbox"/> a. Marketer who directs shipment of off-specification used oil to off-specification used oil burner</p> <p style="padding-left: 20px;"><input type="checkbox"/> b. Marketer who first claims the used oil meets the specifications</p> <p>5. <input type="checkbox"/> Used Oil generator that gives or sells specification used oil to others to burn (Please list burner(s) name & address): _____</p> <p>6. <input type="checkbox"/> Used Oil generator that sends used oil to be re-refined</p> <p>7. <input type="checkbox"/> Used Oil Collection Facility</p>
<p>D. Eligible Academic Entities with Laboratories – Notification for opting into or withdrawing from managing laboratory hazardous wastes pursuant to 40 CFR Part 262 Subpart K (see item by item instructions for eligibility criteria)</p> <p>1. Opting into or currently operating under 40 CFR Part 262 Subpart K for the management of hazardous wastes in laboratories</p> <p style="padding-left: 20px;"><input type="checkbox"/> a. College or University</p> <p style="padding-left: 20px;"><input type="checkbox"/> b. Teaching Hospital that is owned by or has a formal written affiliation agreement with a college or university</p> <p style="padding-left: 20px;"><input type="checkbox"/> c. Non-profit Institute that is owned by or has a formal written affiliation agreement with a college or university</p> <p>2. <input type="checkbox"/> Withdrawing from 40 CFR Part 262 Subpart K for the management of hazardous wastes in laboratories</p>	

VT HAZARDOUS WASTE HANDLER SITE ID INFORMATION & FORM EXAMPLE

EPA ID No.		
11. Description of Hazardous Wastes: Please list the waste name, waste codes and estimated monthly quantity of the hazardous waste handled at your site. Use all waste codes for each waste stream (federal waste codes take precedence over state waste codes). Use an additional page if more spaces are needed. For long lists, please list waste codes in alphanumeric order.		
Waste Name	EPA/State Waste Codes	
Petroleum naphtha parts washer solvent	D001/VT02	
Oil-soaked absorbents	VT02	
gasoline-soaked absorbents	D001/D018	
12. Does your company own other facilities or have affiliates in Vermont? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If yes, please list name(s) & location(s):		
13. Comments: Note: Batteries, fluorescent bulbs, antifreeze for recycling managed according to exemption in Hazardous Waste regulations.		
14. Certification. I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.		
Signature of owner, operator, or an authorized representative	Name and official title (type or print) of owner, operator, or an authorized representative	Date Signed (mm-dd-yyyy)
<i>Will B. Greene</i>	Will B. Greene, Service Mgr	12/01/2014

Hazardous Waste Compatibility List

RCRA'S CHEMICAL WASTE COMPATIBILITY LIST

The mixing of Group A materials with Group B materials may have the potential consequences noted.

Group 1-A

Acetylene sludge
Alkaline caustic liquids
Alkaline cleaner
Alkaline corrosive liquids
Alkaline corrosive battery fluid
Caustic wastewater
Lime sludge and other corrosive alkalies
Lime wastewater
Lime and water
Spent caustic

POTENTIAL CONSEQUENCES: HEAT GENERATION; VIOLENT REACTION

Group 2-A

Aluminum
Beryllium
Calcium
Lithium
Magnesium
Potassium
Sodium
Zinc powder
Other reactive metals and metal hydroxides

POTENTIAL CONSEQUENCES: FIRE OR EXPLOSION; GENERATION OF FLAMMABLE HYDROGEN GAS

Group 3-A

Alcohols
Water

Group 1-B

Acid sludge
Acid and water
Battery acid
Chemical cleaners
Electrolyte, acid
Etching acid liquid or solvent
Pickling liquor & other corrosive acids
Spent acid
Spent mixed acid
Spent sulfuric acid

Group 2-B

Any waste in Group 1-A or 1-B

Group 3-B

Any concentrated waste in Groups 1A or 1B
Calcium
Lithium
Metal hydrides
Potassium
SO₂Cl₂, SOCl₂, PCI₃, CH₃SiCl₃
Other water-reactive waste

POTENTIAL CONSEQUENCES: FIRE, EXPLOSION, OR HEAT GENERATION; GENERATION OF FLAMMABLE OR TOXIC GASES

HAZARDOUS WASTE COMPATIBILITY LIST

Group 4-A

Alcohols
Aldehydes
Halogenated hydrocarbons
Nitrated hydrocarbons
Unsaturated hydrocarbons
Other reactive organic compounds & solvents

POTENTIAL CONSEQUENCES: FIRE, EXPLOSION, OR VIOLENT REACTION

Group 4-B

Concentrated Group 1-A or 1-B wastes
Group 2-A wastes

Group 5-A

Spent cyanide and sulfide solutions

POTENTIAL CONSEQUENCES: GENERATION OF TOXIC HYDROGEN CYANIDE OR HYDROGEN SULFIDE GAS

Group 5-B

Group 1-B wastes

Group 6-A

Chlorates
Chlorine
Chlorites
Chromic acid
Hypochlorites
Nitrates
Nitric acid, fuming
Perchlorates
Permanganates
Peroxides
Other strong oxidizers

POTENTIAL CONSEQUENCES: FIRE, EXPLOSION, OR VIOLENT REACTION

Group 6-B

Acetic acid and other organic acids
Concentrated mineral acids
Group 2-A wastes
Group 5-A wastes
Other flammable and combustible wastes

Hazardous Waste Manifest Information & Form Example

A manifest is a multiple copy shipping form that is used to track the movement of hazardous waste from its place of generation to its final destination (which should be a permitted treatment, storage and/or disposal facility). Conditionally exempt generators (CEG) that self-transport their own waste are not required to use a manifest; however, if a CEG uses a permitted commercial transporter to transport hazardous waste to a certified treatment, storage or disposal facility (TSDf), the transporter will likely require the use of a manifest and consequently, the CEG must comply with the manifest instructions.

Every shipment of hazardous waste from Small Quantity and Large Quantity Generators must be accompanied by a Uniform Hazardous Waste Manifest, and for some wastes must also have a one-time Land Disposal Restriction (LDR) form to certify the waste meets certain pre-disposal treatment standards.

In most cases, your hazardous waste transporter will help you with the process of selecting a TSDf and completing manifests/LDR forms. Although you may only be asked by your transporter to sign the manifest, you are responsible for all of the information on it. It is a good idea to check the form to make sure the information is correct and complete. Instructions on how to complete a manifest can be found in the Vermont Hazardous Waste Management Regulations which can be found on-line by searching key words 'Vermont Hazardous Waste Management Regulations'.

After your transporter has accepted your waste, he or she will also sign the manifest form and give you your copies. Make sure you are given the correct copies. The copies are numbered and have printed on them where they are to be sent.

The accompanying sample manifest is for a hypothetical vehicle service facility in Vermont using a Massachusetts hazardous waste transporter to ship waste to a TSDf in Connecticut. As of September 5, 2006 the U.S. EPA requires the use of the same manifest form nationwide.

For more information on manifests and where to obtain forms (including continuation sheets), visit the DEC's Waste Management & Prevention Division website.

The Environmental Assistance Office or the Waste Management Division can provide a list of permitted transporters. Contact the EAO at 800- 974-9559 or the WMD at 802-828-1138.

HAZARDOUS WASTE MANIFEST INFORMATION & EXAMPLE FORM

Please print or type. (Form designed for use on elite (12-pitch) typewriter.)

Form Approved. OMB No. 2050-0039

UNIFORM HAZARDOUS WASTE MANIFEST		1. Generator ID Number VTD012345678	2. Page 1 of 1	3. Emergency Response Phone 802-123-4567	4. Manifest Tracking Number 000110763 ABC					
5. Generator's Name and Mailing Address Fender Bender Autobody, Inc. 123 Dingsanddents Drive, Pothole, Vermont 05123-1234		Generator's Site Address (if different than mailing address)								
Generator's Phone: 802-123-4567										
6. Transporter 1 Company Name On The Road Transport, Inc.				U.S. EPA ID Number NJD012345678						
7. Transporter 2 Company Name Stay-Put Transport, Inc.				U.S. EPA ID Number NJD012345679						
8. Designated Facility Name and Site Address All Gone, Inc. 21 Roadways End Cleveland, Ohio 87654				U.S. EPA ID Number OHD012345670						
Facility's Phone:										
GENERATOR	9a. HM	9b. U.S. DOT Description (including Proper Shipping Name, Hazard Class, ID Number, and Packing Group (if any))		10. Containers No. Type		11. Total Quantity	12. Unit Wt./Vol.	13. Waste Codes		
		1. State-regulated oily solids (VT Regulated Wastes)		001 DM		265	P	VT02		
		2. Waste Flammable solid, inorganic, N.O.S. (Benzene) 4.1, UN3178, PG II		001 DM		500	P	D001 D018		
		3. Waste Petroleum Distillates, N.O.S., 3, UN1268, PG II		001 DM		55	G	D001 VT02		
		4.								
14. Special Handling Instructions and Additional Information 1. Oil soaked absorbents 2. gasoline- soaked absorbents 3. Petroleum Naphtha Parts Cleaning Solvent										
15. GENERATOR'S/OFFEROR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by the proper shipping name, and are classified, packaged, marked and labeled/placarded, and are in all respects in proper condition for transport according to applicable international and national governmental regulations. If export shipment and I am the Primary Exporter, I certify that the contents of this consignment conform to the terms of the attached EPA Acknowledgment of Consent. I certify that the waste minimization statement identified in 40 CFR 262.27(a) (if I am a large quantity generator) or (b) (if I am a small quantity generator) is true.										
Generator's/Offoror's Printed/Typed Name Will B. Greene				Signature Will B. Green		Month Day Year 11 30 15				
16. International Shipments <input type="checkbox"/> Import to U.S. <input type="checkbox"/> Export from U.S. Port of entry/exit: _____ Transporter signature (for exports only): _____ Date leaving U.S.: _____										
TRANSPORTER	17. Transporter Acknowledgment of Receipt of Materials									
	Transporter 1 Printed/Typed Name Joe Transporter				Signature Joe Transporter		Month Day Year 11 30 15			
	Transporter 2 Printed/Typed Name Antonia Hauler				Signature Antonia Hauler		Month Day Year 12 06 15			
DESIGNATED FACILITY	18. Discrepancy									
	18a. Discrepancy Indication Space <input type="checkbox"/> Quantity <input type="checkbox"/> Type <input type="checkbox"/> Residue <input type="checkbox"/> Partial Rejection <input type="checkbox"/> Full Rejection									
	Manifest Reference Number: _____									
	18b. Alternate Facility (or Generator)						U.S. EPA ID Number			
	Facility's Phone: _____									
18c. Signature of Alternate Facility (or Generator)									Month Day Year	
19. Hazardous Waste Report Management Method Codes (i.e., codes for hazardous waste treatment, disposal, and recycling systems)										
1. H141			2. H141			3. H141			4.	
20. Designated Facility Owner or Operator: Certification of receipt of hazardous materials covered by the manifest except as noted in Item 18a										
Printed/Typed Name Rosa Recycler				Signature Rosa Recycler		Month Day Year 12 07 15				

EPA Form 8700-22 (Rev. 3-05) Previous editions are obsolete.

DESIGNATED FACILITY TO DESTINATION STATE (IF REQUIRED)

